

KEYSTONE ELECTRONICS CORP. AND ITS AFFILIATES SHALL NOT BE REPRODUCED, DISTRIBUTED, COPIED, OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.

REEL DIA. REF.

FEED DIRECTION

.500 [12.7] DIA. HOLE THRU

$\pm .005$ [± 0.15]

PITCH

$\pm .005$ [± 0.15]

.157 [4.0]

$\pm .005$ [± 0.15]

$\emptyset .059$ [$\emptyset 1.50$] DIA. HOLE (TYP.)

.079 [2.0]

.659 [16.73] REF.

$\pm .005$ [± 0.15]

WIDTH

FEED DIRECTION

.016 [0.4] REF.

TAPE AND REEL SPECIFICATIONS:

- MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD
3.47 [88.0] WIDE; 1.10 [28.0] PITCH

- 15.0 [380.77] DIA. 200 PIECES OF
PART NO. 1024 PER REEL.

3.21.12	CHANGE AS PER ECN 12-035	A
DATE	DESCRIPTION	REV.

KEYSTONE ELECTRONICS CORP. www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900			
PART NAME SM BATTERY HOLDER AA, ON TAPE			
MATERIAL AS NOTED			
FINISH AS NOTED		DRN BY NT	DATE 2.03.11
		APP'D LN	SCALE X
TOLERANCES INCH [MM] DECIMAL $\pm .015$ [± 0.38] ANGULAR $\pm 1^\circ$ UNLESS OTHERWISE SPECIFIED	CODE C/M	DWG NO. 1024TR	