



### Bestückungsplan / contact layout

■ bestückt / assembled



### Leiterplatten-Lochbild / PCB drillhole pattern



Elastische Einpresszone mit Übergabesteckzone /  
compliant pressfit zone with mating transfer zone

Isolierwerkstoff / housing material : PBT GF30

Bauart 7 / type 7

Anforderungsstufe 1 = 500 Steckzyklen / performance class 1 = 500 mating cycles



Fehlende Masse und Angaben nach IEC 60 603-2 / DIN EN 60 603-2

Missing information and dimensions per IEC 60 603-2 / DIN EN 60 603-2

Schichtaufbau im metallisierten Loch siehe Zeichnung 164062/Nr.6

diameter of drilled hole see drawing 164062/No.6

- 1)  $\phi 1,0 \pm 0,09$  Durchmesser des metallisierten Loches  
 $\phi 1,0 \pm 0,09$  Diameter of finished plated-through hole
- $\phi 1,15 \pm 0,025$  Bohrungsdurchmesser des Loches  
 $\phi 1,15 \pm 0,025$  Diameter of drilled hole

Information:	Tolerances		Scale	2:1
	All Dimensions in mm			
All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.	Subject to modification without prior notice. Drawing will not be updated.		Designation	
	 www.ERNI.com		Federleiste C 96 EE Fem. Connector C 96 Pressfit	
Index	Date	H:00062233.SZA	284135	I
Consider protection memo from DIN 34			STVC	

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[284135](#)