




THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2012/10/25	Ruru	PLD-04BFMA-QL7002 To PLD-04BFMA-QL7002
B	LEN1510154	2015/01/08	Vicky	Update Logo & Tolerance



- Note:
- * Important Dimension To Check.
 - * Waterproof Rate: IP67.
 - * Housing: Nylon,UL 94V-0, Black.
 - * Male Pin: Copper Alloy, Gold Plated.
 - * Nut : Nylon+25%GF, UL 94V-0, Black.
 - * Clamp Ring: Nylon+GF, UL 94V-2, Black.
 - * Sealing Nut: Nylon+GF, UL 94V-2, Black.
 - * Rubber Parts: Silicone, UL 94V-0, Gray.
 - * Seals for Cable OD: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$.
 - * Operating Voltage Max: AC 300 V Rms.
 - * Operating Current Max: 5A.
 - * One Set Unassembled In One Bag.

UNIT:mm		TITLE		ITEM NO		DRAWN BY		DATE	
TOLERANCE		ASSY,PUSH LOCK,4PIN F CONN M PIN		PLD-04BFMA-QL7002		Vicky		2015-01-08	
$\pm 0.5 \text{ mm}$		SCALE 3:2	SIZE A4	DWG NO	PLD-04BFMA-QL7002	CHECKED BY	Sam	DATE	2015-01-08
		REV. B	WC-REV. A.2	CUSTOMER	ALTW	APPROVED BY	Rita	DATE	2015-01-08
		Inspection item							

Amphenol LTW
安費諾亮泰企業股份有限公司

FWW10702-01-02A1