




Series 80 Mighty Mouse Contacts and Tools Jam Nut Tightening Tools Connector Holding Fixtures

A

Spanner tool for tightening Series 80 jam nuts



Use these tools to tighten Series 80 jam nuts. 1/4" or 3/8" square drive for use with torque wrenches. Heat-treated steel, nickel plated.


| Shell Size | Spanner Tool Part Number | | | | | |
|------------|--------------------------|------------|------------|---------------------|---------------------|------------|
| | Series 800 | Series 801 | Series 803 | Series 804 Style 07 | Series 804 Style 00 | Series 805 |
| 5 | 600-146-01 | 600-146-02 | 600-137-05 | 600-146-03 | 600-147-5 | — |
| 6 | 600-146-02 | 600-146-03 | 600-137-06 | 600-146-04 | 600-147-6 | — |
| 7 | 600-146-03 | 600-146-05 | 600-137-07 | 600-146-06 | 600-147-7 | — |
| 8 | 600-146-04 | 600-146-05 | 600-137-08 | 600-146-06 | 600-147-7 | 600-154-08 |
| 9 | 600-146-05 | 600-146-06 | 600-137-09 | 600-146-07 | 600-147-9 | 600-154-09 |
| 10 | 600-146-06 | 600-146-07 | 600-137-10 | 600-146-08 | 600-147-10 | 600-154-09 |
| 11 | — | 600-146-08 | — | — | — | 600-154-11 |
| 12 | 600-146-08 | — | 600-137-12 | 600-146-10 | 600-147-12 | 600-154-12 |
| 13 | — | 600-146-10 | — | — | — | — |
| 14 | 600-146-10 | — | 600-137-14 | 600-146-12 | 600-147-14 | — |
| 15 | 600-146-11 | — | 600-137-15 | 600-146-13 | 600-147-15 | 600-154-15 |
| 16 | — | 600-146-13 | — | — | — | — |
| 17 | — | 600-146-14 | — | — | — | — |
| 18 | — | — | — | — | — | 600-154-18 |
| 19 | — | — | — | — | — | 600-154-19 |
| 21 | — | 600-146-17 | — | — | — | — |
| 23 | — | — | — | — | — | 600-154-23 |

See Table I for torque values

To order as a kit replace dash number with connector series i.e.: substitute 600-146-01 with 600-146-801.

Kit consists of all connector family shell size tools

Spanner tool for tightening Series 80 size #8 jam nuts



These Lengthened spanner tools are used to tighten jam nuts on extended-length connectors with size #8 contacts. 3/8" square drive. Nickel-plated heat-treated steel.

| Size #8 Spanner Tool Part Number | | | |
|----------------------------------|------------------------------|------------------------------|-------------------------|
| Part No. | Series 801 Series Shell Size | Series 805 Series Shell Size | Jam Nut Thread Size Ref |
| 600-197-05 | 8 | N/A | .562 |
| 600-197-07 | N/A | 10 | .688 |
| 600-197-13 | 16 | N/A | 1.062 |
| 600-197-14 | 17 | N/A | 1.125 |
| 600-197-15 | N/A | 18 | 1.188 |
| 600-197-16 | 19 | 19 | 1.250 |
| 600-197-17 | 21 | 21 | 1.375 |
| 600-197-18 | N/A | 23 | 1.500 |

See Table I for torque values

To order as a kit replace dash number with connector series i.e.: substitute 600-197-01 with 600-197-801

Kit consists of all connector family shell size tools

Dimensions in Inches (millimeters) are subject to change without notice.

Series 80 Mighty Mouse Contacts and Tools

Jam Nut Tightening Tools, Connector Holding Fixtures and Mighty Mouse Recommended Torque Values,



Connector holding tool for tightening backshells and accessories

1 Plug tool for holding Series 80 plug connectors. Heat-treated steel, nickel plated.

2 Receptacle tool for holding Series 80 receptacle connectors. Heat-treated steel, nickel plated.



1



2

| Holding Tool Part Number (Add P or R) | | | | | | | | |
|---------------------------------------|--------------|---------------|--------------|--------------|--------------|---|---|---|
| Shell Size | Series 800 | Series 801 | Series 803 | Series 804 | Series 805 | | | |
| 5 | 600M005-05 ★ | 600MM005-05 ◆ | 600-140-5 ★ | 600-141-5 ■ | — | — | — | — |
| 6 | 600M005-06 ★ | 600MM005-06 ◆ | 600-140-6 ★ | 600-141-6 ■ | — | — | — | — |
| 7 | 600M005-07 ★ | 600MM005-07 ◆ | 600-140-7 ★ | 600-141-7 ■ | — | — | — | — |
| 8 | 600M005-08 ★ | 600MM005-08 ◆ | 600-140-8 ★ | 600-141-8 ■ | 600-185-8 ○ | — | — | — |
| 9 | 600M005-09 ★ | 600MM005-09 ◆ | 600-140-9 ★ | 600-141-9 ■ | 600-185-9 ○ | — | — | — |
| 10 | 600M005-10 ★ | 600MM005-10 ◆ | 600-140-10 ★ | 600-141-10 ■ | 600-185-10 ○ | — | — | — |
| 11 | — | — | — | — | 600-185-11 ○ | — | — | — |
| 12 | 600M005-12 ★ | — | 600-140-12 ★ | 600-141-12 ■ | 600-185-12 ○ | — | — | — |
| 13 | — | 600MM005-13 ◆ | — | — | — | — | — | — |
| 14 | — | — | 600-140-14 ★ | 600-141-14 ■ | — | — | — | — |
| 15 | — | — | 600-140-15 ★ | 600-141-15 ■ | 600-185-15 ○ | — | — | — |
| 16 | — | 600MM005-16 ◆ | — | — | — | — | — | — |
| 17 | — | 600MM005-17 ◆ | — | — | — | — | — | — |
| 18 | — | — | — | — | 600-185-18 ○ | — | — | — |
| 19 | — | — | — | — | 600-185-19 ○ | — | — | — |
| 21 | — | 600MM005-21 ◆ | — | — | — | — | — | — |
| 23 | — | — | — | — | 600-185-23 ○ | — | — | — |

- ★ Add **P** for plug holder or **R** for receptacle holder, followed by polarizing position (**N, X, Y, Z**).
- ◆ Add **P** for plug holder or **R** for receptacle holder, followed by polarizing position (**A, B, C, D**).
- Add **P** for plug holder or **R** for receptacle holder, followed by polarizing position (**A, B, C, D, E, F**). Omit for single master key).
- Add **P** for plug holder or **R** for receptacle holder, followed by polarizing position (**A, B, C, D, E, F**). Omit polarization for receptacle tools.

The following tabulations show the changes to the Glenair recommended torque values for connector coupling torque and backshell tightening torque. The jam nut tightening torque values will remain the same.

| Series 800 Recommended Torque Values | | |
|--------------------------------------|----------------------|------|
| Series 800 | Backshell Tightening | |
| | In-Lbs. | |
| | Min. | Max. |
| 5 | 12 | 16 |
| 6 | 14 | 18 |
| 7 | 16 | 20 |
| 8 | 18 | 22 |
| 9 | 20 | 24 |
| 10 | 22 | 26 |
| 12 | 26 | 30 |

| Series 801, 802, 803, 804, 805 Recommended Torque Values | | | |
|--|-----------------------|------------------------------|------|
| Shell Size Series 801, 802, 803 | Shell Size Series 805 | Backshell Tightening In-Lbs. | |
| | | Min. | Max. |
| | | 5 | - |
| 6 | 8 | 14 | 18 |
| 7 | 9 | 16 | 20 |
| 8 | 10 | 18 | 22 |
| 9 | 11 | 20 | 24 |
| 10 | 12 | 22 | 26 |
| 12, 13 | 15 | 28 | 32 |
| 14, 16 | 18 | 28 | 32 |
| 15, 17 | 19 | 28 | 32 |
| 21 | 23 | 28 | 32 |

Dimensions in Inches (millimeters) are subject to change without notice.