

VGA with Audio over Cat5/Cat6 Extender, Receiver, USB-Powered, 1920x1080 at 60Hz, Up to 750-ft., TAA

MODEL NUMBER: **B132-100A-MR**



Description

Tripp Lite's B132-100A-MR VGA with Audio over Cat5 Extender Receiver Unit is designed to work with Tripp Lite's [B132-002A-2](#) and [B132-004A-2](#) VGA with Audio over Cat5 Extender / Splitter Transmitter Units. Unlike the [B132-100A](#) Receiver Unit, which supports distances up to 1,000-ft, the B132-100A-MR is a cost effective solution for distances up to 750-ft. It extends a 1920 x 1080 video and audio signal up to 300-ft. from the source, or a 1024 x 768 video and audio signal up to 750-ft. Power is supplied via the included USB Micro-B cable, with no external power supply required. Connect the included Micro-B cables between the Receiver and a USB port on a computer, monitor, or USB wall charger, such as the Tripp Lite [U280-W01-QC3](#). It also features equalization and gain controls to adjust the video image. Audio connections are made with standard 3.5mm stereo cables (not included). Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- Works with a [B132-002A-2](#) or [B132-004A-2](#) local unit to extend a VGA video and audio signal up to 750-ft. from the source
- Extends a 1920 x 1080 video and audio signal up to 300-ft, or a 1024 x 768 video and audio signal up to 750-ft.
- 24AWG, Solid Wire Cat5e/6 cable (such as Tripp Lite's N202-Series Cat6 cables) is required to achieve maximum distance and resolution
- Power is supplied via the included USB Micro-B cable; no external power supply required
- Features built-in equalization and gain controls to adjust the video image.
- All operating systems supported
- Plug and play; no software or drivers required
- HDCP and EDID compliant
- Ideal for digital signage installations for retail, schools, churches, etc.
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

Highlights

- Extends a 1920 x 1080 video and audio signal up to 300-ft, or a 1024 x 768 video and audio signal up to 750-ft.
- EDID copy feature stores the monitor's EDID information and sends it to the connected computer, ensuring optimal display compatibility
- Power is supplied via the included USB Micro-B cables; no external power supplies required
- Plug and play, no software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Package Includes

- B132-100A-MR
- USB Micro-B cable
- Screwdriver for EQ/Gain adjustment
- Owner's Manual



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

PHYSICAL	
Shipping Weight (lbs.)	1
Shipping Weight (kg)	0.45
Unit Dimensions (hwd / in.)	1 x 2.5 x 3.6
Unit Dimensions (hwd / cm)	2.54 x 6.35 x 9.14
Unit Weight (lbs.)	0.45
Unit Weight (kg)	0.20
Color	Black
COMMUNICATIONS	
Max 1024 x 768 Range (ft)	750
Max 480P Range (ft)	750
Max 1440 x 900 Range (ft)	300
Max 1080i Range (ft)	300
Max 1080P Range (ft)	300
Max 480i Range (ft)	750
Max 640 x 480 Range (ft)	750
Max 800 x 600 Range (ft)	750
Max 1600 x 1200 Range (ft)	300
Max 720P Range (ft)	300
CONNECTIONS	
Ports	1
Side A - Connector 1	RJ45 (FEMALE)
Side B - Connector 1	HD15 (FEMALE)
Side B - Connector 2	3.5MM (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>