

6 5 4 3 2 1

E

D

C

B

A

F3 MAX-LOC NUT

STAINLESS STEEL
SCREWS W/FLAT
WASHER 1¹/₂
AND O'RING

STAINLESS STEEL
SCREWS W/LOCK
WASHER
(8) REQ'D

MOMENTARY SWITCH (THREE SPEED)
(505SW-3)

MOMENTARY SWITCH (THREE SPEED)
(505SW-3)

MOMENTARY SWITCH (THREE SPEED)
(505SW-3)

BLANK

MAINTAINED E-STOP SWITCH
(505B-RM)

14.50
(368.3)

1.18
(29.9)

BETWEEN CENTERS

3.52
(89.4)

STAINLESS STEEL
SUPPORT RINGS
(2) REQ'D

2.31
(58.7)

NOTES:
1. INSTALLATION INSTRUCTIONS, BUTTON ID. LABELS. ARE PACK WITH THE PART.
2. ALL BUTTONS ARE HIGH AMBIENT, CHEMICALLY RESISTANT
MATERIAL - COLOR BLACK

CUSTOMER DRAWING
EC NO: WNA2010-0556
DRWN: TVICKERS 2010/03/05
CHKD: DW
APPR: DTITUS 2010/04/28
DESCRIPTION
REV

QUALITY
SYMBOLS
▽=0
▽C=0

GENERAL TOLERANCES
(UNLESS SPECIFIED)

	mm	INCH
4 PLACES	±---	±---
3 PLACES	±---	±.005
2 PLACES	±0.13	±.010
1 PLACE	±0.25	±.020

ANGULAR ±.5°

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
IN/MM

DRAWN BY DATE
TVICKERS 2010/03/05

CHECKED BY DATE
DW 2010/03/05

APPROVED BY DATE
DTITUS 2010/04/27

MATERIAL NO.
1301260324

SIZE
A

SCALE
NTS

DESIGN UNITS
INCH

THIRD ANGLE
PROJECTION

TITLE
5058 W/(3) 505SW-3
BLANK & 505B-RM

MOLEX INCORPORATED

DOCUMENT NO.
SD-130126-038

SHEET NO.
1 OF 1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

6 5 4 3 2 1