

PX Serial Remote KVM Access

MODEL NUMBER: 0SU70033



Description

Non-blocking serial device access

The PX Serial is a palm-sized, single port RS232 device providing non-blocking remote access for any number of remote users to any number of individual serial devices including headless servers, routers, managed network switches, serially-based power management devices, and telecommunications/telephone exchange systems. The device comes with a range of mounting options for complete installation flexibility.

Complete access to your computer - any time, anywhere

PX Serial is a high performance IP Gateway providing complete BIOS level remote access and control of your server, from any location. Compact and cost-effective, the PX Serial comes with 256 AES security as standard, and is equally adept in small business environments, remote support applications, and Enterprise data centers. Whatever your circumstance, wherever your computer, PX Serial gives you the confidence of complete access and control, always.

Complete remote support for mission critical applications

PX Serial is an indispensable tool for remotely supporting mission-critical computers and devices - where every instant of added downtime may be critical to service provision. PX Serial lets you instantly access the remote computer's BIOS, and accurately diagnose and even fix system faults - saving you the time and cost of a field technician roll out. PX Serial is ideal for market applications running mission critical services on a single computer/server such as medical, telecom, security, Software as a Service, and banking and finance.

Scalable centralized management

The single-port PX Serial handily solves the problem of blocked server access in the data center. With a number of PX Serial devices connected, multiple remote users can control multiple servers, all at the same time. Additional PX Serial devices can be added as your data center grows.

Highlights

- Single port, palm-sized device
- BIOS level access over IP connection
- Management system enabled
- Cost-effective & easily scalable
- Ideal for isolated/widely distributed servers
- Supports data rates from 110 bps to 460.8 Kbps
- Supports ICMP, IP, TCP, UDP, DHCP, BootP, ARP / RARP, DNS, SNMP MIB II, HTTPS, SSH
- Built-in 1.5 KV magnetic isolation
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

- Supports data rates from 110 bps to 460.8 Kbps
- Supports ICMP, IP, TCP, UDP, DHCP, BootP, ARP / RARP, DNS, SNMP MIB II, HTTPS, SSH

Package Includes

- PX Serial
- Power Supply
- Mounting Kit Footpads
- CD



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Features

- Single port, palm-sized device
- BIOS level access over IP connection
- Management system enabled
- Cost-effective & easily scalable
- Ideal for isolated/widely distributed servers
- Supports data rates from 110 bps to 460.8 Kbps
- Supports ICMP, IP, TCP, UDP, DHCP, BootP, ARP / RARP, DNS, SNMP MIB II, HTTPS, SSH
- Built-in 1.5 KV magnetic isolation
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
Accessories Type	Remote Management
PHYSICAL	
Color	Silver
ENVIRONMENTAL	
Storage Temperature Range	-20 to 85 C / -4 to 185 F
Relative Humidity	5 to 95% Non-Condensing
Operating Temperature	-10 to 70 C / 14 to 158 F
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>