

**NEW**



General Purpose Gigabit Transmission  
Metric System Connector


CONNECTOR

MB-0206-1

August 2010

## MJ06 Series

**RoHS Compliant**



The MJ06 Series is a high-speed signal connector for differential transmission, compatible with backplane/midplane type devices. It has superior high-speed transmission performance, with a balanced transmission structure that is ideal for differential transmission and allows for a simplified mounting pattern design.

### Features

- Compatible with IEC61076-4-101 mounting dimensions. Usage is possible with the same standard connectors (known as HM connectors).
- Pair signal alignment (side pair, 1.8mm pitch) and ground structure, optimized for high-speed differential transmission
- Symmetrical pin structure prevents skew between differential signal pair.
- Press-fit attachment to board for both pin side and socket side connector (finished diameter compatible with 0.6mm dia.)
- Through-hole location to optimize board wiring pattern.
- Compatible with connector height 9mm max. from board, minimum slot distance 17mm.
- Available in cable connection type. (Please contact us for more information.)


### Applications

- Factory automation equipment, semiconductor manufacturing equipment, various inspection and measuring devices, server/storage devices, communication/network devices, broadcasting equipment, medical equipment, etc.

### General Specifications

- No. of Contacts: 120 pos. (signal + ground / module)
- Differential Impedance:  $100\Omega \pm 15\Omega$  ( $T_r=100\text{ps}$  [10-90%])
- Crosstalk: 5% max. ( $T_r=100\text{ps}$  [10-90%])
- Rated Voltage: AC200 Vr.m.s
- Rated Current: 1A
- Operating Temperature: -35 to 85 Deg. C
- Compliant Pin: single insertion force 100N max. / single retention force 10N min. (after test)
- Applicable Board Thickness: 1.4mm to 5.0mm

# MJ06 Series Mating Operation



## Materials and Finishes

### Pin Connector

Component	Material / Finish
Insulator	Glass filled PBT (white)
Contact	Copper alloy / Contact area: Au plating over Ni Terminal area: Au flash plating over Ni (Note) Pin contact and ground contact in common

### Socket Connector

Component	Material / Finish
Insulator	Glass filled PBT (white)
Contact	Copper alloy / Contact area: Au plating over Ni Terminal area: Au flash plating over Ni (Note) Socket contact and ground plate in common

### Board Through-Hole Specification (for reference)

Board Material	Glass fabric filled laminated epoxy board
Board Thickness	1.4mm to 5.0mm
Finished Diameter (Au flash plating over copper)	0.6mm dia. ± 0.05mm
Copper Plating Thickness	20 μm (min.)
Prepared Hole Drilled Diameter	0.7mm dia. ± 0.025mm

Ordering Information

Angle Socket

MJ06-120 F R P

Series

Connection Method: P = Pressfit

Connection Direction: R = Right Angle, S = Straight

Product Configuration: F = Socket Contact, M = Pin Contact, S = Shroud

No. of Contacts: 120 pos.

Straight Pin Header

MJ06-120 M S P-A 0-A

No. of Contacts: 120 pos.

Product Identification Mark

Applicable Board Thickness: 0 = 1.4mm min. (shroud attachment) 3 =  $t3.5 \pm 0.3$  (mm) (shroud attachment) 5 =  $t5.0 \pm 0.4$  (mm)

Insulator Shape: A = for Angle socket

Connection Method: P = Press-fit

Connection Direction: R = Right Angle, S = Straight

Product Configuration: F = Socket Contact, M = Pin Contact, S = Shroud

Angle Pin Header

MJ06-120 M R P-1

No. of Contacts: 120 pos.

Mating Lock: 1 = One-action type

Connection Method: P = Pressfit

Connection Direction: R = Right Angle, S = Straight

Product Configuration: F = Socket Contact, M = Pin Contact, S = Shroud



Shroud

MJ06-120 S

No. of Contacts: 120 pos.


Product Configuration: F = Socket Contact, M = Pin Contact, S = Shroud

◆MJ06-120FRP (Angle Socket)





Applicable Board Dimensions (for reference)


◆MJ06-120MSP-A0-A (Pin Header Short)




◆MJ06-120MSP-A3-A (Pin Header Long)



◆MJ06-120MSP-A5-A (Pin Header Long)






◆MJ06-120MRP-1 (Angle Pin Header)



Applicable Board Dimensions (for reference)



◆MJ06-120S (Shroud)



Applicable Board Dimensions (for reference)

## SJ Drawing

Configuration	Part Number	SJ Drawing No.	Specification
Angle Socket	MJ06-120FRP	SJ108443	JACS-10524
Straight Pin Header	MJ06-120MSP-A0-A	SJ108444	
	MJ06-120MSP-A3-A	SJ108446	
	MJ06-120MSP-A5-A	SJ108447	
Angle Pin Header	MJ06-120MRP-1	SJ108452	
Shroud	MJ06-120S	SJ108448	

**Notice:** Products shown in this leaflet are made for the applications listed below. However, if the above-mentioned products are to be used in aerospace devices, marine cable-connection devices, atomic power control systems, medical equipment for life-support systems, or any other specific application requiring extremely high reliability, please contact JAE for further information.

Recommended applications: computers, office machines, measuring devices, telecommunication devices (terminals, mobile devices), AV devices, household applications, FA devices, etc.

## Japan Aviation Electronics Industry, Limited

Product Marketing Division

Aobadai Building, 3-1-19, Aobadai, Meguro-ku, Tokyo 153-8539

Phone: +81-3-3780-2787 FAX: +81-3-3780-2946

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## JAE Electronics:

[MJ06-004FSH](#) [MJ06-004FSH-SHL-500](#) [MJ06-012C](#) [MJ06-012C-R](#) [MJ06-012C-SHL](#) [MJ06-024S](#) [MJ06-048S](#)  
[MJ06-120FRP](#) [MJ06-120MRP-1](#) [MJ06-120MRP-2](#) [MJ06-120MSP-A0-A](#) [MJ06-120MSP-A3-A](#) [MJ06-120MSP-A5-A](#)  
[MJ06-120MSP-A5-C](#) [MJ06-120MSP-A5-D](#) [MJ06-120MSP-A5-E](#) [MJ06-120MSP-A5-F](#) [MJ06-120MSP-A5-G](#) [MJ06-120MSP-H0-A](#) [MJ06-120S](#) [MJ06-R](#)