


# Fusible & Anti-Explosion Type

Normal & Miniature Style [ FAE Series ]



## **INTRODUCTION**

FAE series is wirewound resistor capable of acting both as a regular resistor, and as a fuse when an abnormal current is received. There will be no flames, no explosion, no sound and no arc happened when fusing. FAE series offers space saving and a cost advantage, and is specifically designed to meet customer's requirements.


## **FEATURES**

Power Rating	1/2W, 1W, 2W, 3W
Resistance Tolerance	±1%, ±5%
T.C.R.	±300ppm/°C
Flameproof Multi-layer Coating Meets	UL-94V-0
Flameproof Feature Meets Overload Test	UL-1412

## **DERATING CURVE**

For resistors operated in ambient temperatures above 70°C, power rating must be derated in accordance with the curve below.

## Rated Load (%)



Ambient Temperature (°C)


# **FUSING CHARACTERISTICS**

Fuse within 60 seconds when receiving 25 times the power rating. (Fusing power and time can be designed on customer's request)

Fusing residual resistive value at least 100 times of rated resistance. No flames, no explosion, no sound and no arc occur when fusing.

# **DIMENSIONS**

Unit: mm



STYLE		DIMENSION					
Normal	Miniature	L	øD	н	ød		
-	FAE50S/FAE1SS	6.3±0.5	3.0±0.5	28±2.0	0.55±0.05		
FAE-50	FAEIWS	9.0±0.5	3.8±0.5	26±2.0	0.55±0.05		
FAE100	FAE2WS	11.5±1.0	5.0±0.5	35±2.0	0.8±0.05		
FAE200	FAE3WS	15.5±1.0	5.5±0.5	33±2.0	0.8±0.05		

Note:			

# **ELECTRICAL CHARACTERISTICS**

STYLE	FAE50S	FAEISS	FAE-50	FAEIWS	FAEI00	FAE2WS	FAE200	FAE3WS
Power Rating at 70°C	1/2W	IW	1/2W	IW		2W		3W
Maximum Working Voltage	$\sqrt{PxR}$							
Voltage Proof on Insulation	300V		400V	500V				
Resistance Range	3.3Ω - 100Ω for E24 & E96 series value							
Operating Temp. Range	-55°C to +200°C							
Temperature Coefficient	±300ppm/°C							

Note: Special value is available on request

# **ENVIRONMENTAL CHARACTERISTICS**

PERFORMANCE TEST	TEST METHOD	APPRAISE	
Short Time Overload	IEC 60115-1 4.13	I 0 times rated power for 5 Sec.	±2.0%+0.05Ω
Voltage Proof on Insulation	IEC 60115-1 4.7	in V-block for 60 Sec., test voltage by type	By type
Temperature Coefficient	IEC 60115-1 4.8	-55°C to +155°C	By type
Insulation Resistance	IEC 60115-1 4.6	in V-block for 60 Sec.	>100M
Solderability	IEC 60115-1 4.17	235±5°C for 3±0.5 Sec.	95% Min. coverage
Solvent Resistance of Marking	IEC 60115-1 4.30	IPA for 5±0.5 Min. with ultrasonic	No deterioration of coatings and markings
Robustness of Terminations	IEC 60115-1 4.16	Direct load for 10 Sec. in the direction of the terminal leads	≥2.5kg (24.5N)
Periodic-pulse Overload	IEC 60115-1 4.39	4 times RCWV 10,000 cycles (1 Sec. on, 25 Sec. off)	±1.0%+0.05Ω
Damp Heat Steady State	IEC 60115-1 4.24	40±2°C, 90-95% RH for 56 days, loaded with 0.1 times RCVVV	±5.0%+0.05Ω
Endurance at 70°C	IEC 60115-1 4.25	70±2°C at RCWV for 1,000 Hr. (1.5 Hr. on, 0.5 Hr. off)	±5.0%+0.05Ω
Temperature Cycling	IEC 60115-1 4.19	-55°C ⇒ Room Temp. ⇒ +155°C ⇒ Room Temp. (5 cycles)	±2.0%+0.05Ω
Resistance to Soldering Heat	IEC 60115-1 4.18	260±3°C for 10±1 Sec., immersed to a point 3±0.5mm from the body	±1.0%+0.05Ω
Accidental overload test	IEC 60115-1 4.26	4 times RCWV for 1 Min.	No evidence of flaming or arcing

#### **EXPLANATIONS OF ORDERING CODE**

Code I - 3 **Series Name** 

See Index

Code 4 - 6 **Power Rating** 

-05 = ød0.5mm-06 = ød0.6mm-07 = ød0.7mm-08 = ød0.8mm-10 = ød1.0mm-14 = ød1.4mm-12 = 1/6W-25 = 1/4W25S = 1/4WS-50 = 1/2W50S = 1/2WS100 = 1 WIWS = IWS200 = 2W2WS = 2WS204 = 0.4W207 = 0.6W300 = 3W3WS = 3WS3WM = 3WM400 = 4W500 = 5W5WS = 5WS5SS = 5WSS700 = 7W7WS = 7WS10A = 10W20A = 20W

Code 7 **Tolerance**  $P = \pm 0.02 \%$  $A = \pm 0.05 \%$ 

 $K = \pm 10 \%$ 

- = Base on Spec

B = +0.1%C = +0.25% $D = \pm 0.5 \%$ F = ±1 %  $G = \pm 2 \%$  $1 = \pm 5 \%$ 

Code 8 **Packing Style** 

T = Tape/BoxR = Tape/Reel B = Bulk

Code 9

Temperature Coefficient of Resistance - = Base on Spec.

 $A = \pm 5 \text{ ppm/}^{\circ}\text{C}$  $B = \pm 10 \text{ ppm/}^{\circ}\text{C}$  $C = \pm 15 \text{ ppm/}^{\circ}C$  $S = \pm 20ppm/^{\circ}C$ 

 $D = \pm 25 \text{ ppm/}^{\circ}C$  $E = \pm 50 \text{ ppm/}^{\circ}\text{C}$  $F = \pm 100 \text{ ppm/°C}$ 

 $G = \pm 200 \text{ ppm/}^{\circ}C$  $H = \pm 250 \text{ ppm/°C}$  $I = \pm 300 \text{ ppm/°C}$ 

 $I = \pm 350 \text{ ppm/°C}$ 

Code 10 - 12

Forming Type 26 - 26mm

**52-**

73 - = 73 mm81 - 81 mm

52- = 52.4mm

91 - = 91 mmF = FType

FK = FKType

FKK = FKK Type FFK = F-form Kink

M = M-Type Forming MB = M-form W/flat MT = MT Type Forming

MR = MRTypeAV = AVIsertPN = PANAsert  $\overline{100}R$ 

Code 13 - 17 Resistance Value

0RI = 0.1100R = 10010K = 10.00010M = 10,000,000

**EXCEPTION:** 

• Cement series:

<Code 8>: Special packing style code

30A = 30W40A = 40W50A = 50W10S = 10WS15A = 15W25A = 25W10B = 100W 25B = 250W

B: Bulk with wirewound or metal oxide sub-assembly for resistance value

W: Bulk with ceramic based wirewound sub-assembly for resistance value

M: Bulk with metal oxide sub-assembly for resistance value

F: Bulk with Fiberglass based wirewound sub-assembly for resistance value

<Code 10-12>: Without forming code

Example: SQP500|B-I0R

• JPW series:

<Code 13-17>: without resistance value code

Example: **JPW-06-T-52-**