


SSI-LXH387SID-150







- 1. SSI -I X433SID | FD.
- 2. HOLDER: LXP-SSI-387BSH, LXP-SSI-387BZL.
- 3, ANODE LEAD: LXP-WST24RDTOC STRANDED. CUT 135mm, STRIP 4mm & 9mm.
- 4, CATHODE LEAD: LXP-WST24BLTOC STRANDED. CUT 135mm, STRIP 4mm & 9mm.
- 5. CRIMP LEADS EXTERNAL TO HOUSING. HEAT SHRINK OVER CRIMP-2 PLS.
- 6. PANEL HOLE CUT OUT: 5/16" DIAMETER.

ELECTRO-OPTICAL CH	ARACTERIS	TICS TA=25	.c	I f= 20mA	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		636		nm	
FORWARD VOLTAGE		2.0	2.5	۷f	
REVERSE VOLTAGE	5.0			٧r	1 _r =100µA
AXIAL INTENSITY		60		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		120		2x theta	
EMITTED COLOR:	RED				
EPOXY LENS FINISH:	RED DIFFUSED				

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/ ' C
OPERATING, STORAGE TEMP.	-40 TO +85	•C
SOLDERING TEMP,	+ 260	°C
2.0mm FROM BODY		3 SEC. MAX

* t<10uS

UNCONTROLLED DOCUMENT *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=+DECIMAL PRECISION MAX.= +0.00 (±0.000). LEAD SIZE=±0.05 (±0.000). LEAD SIZE=±0.05 (±0.000). LEAD SIZE=±0.05 (±0.000). MIN=+DECIMAL PRECISION MAX.= +0.00 (±

REV.

PART NUMBER SSI-LXH387SID-150

T-5 FRESNEL LENS PANEL INDICATOR, 636nm SUPER HIGH INTENSITY RED LED, RED DIFFUSED LENS WITH 6" WIRE LEADS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com

TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY:

APPROVED BY: DATE: 8.2.01 1 OF 1 PAGE: SCALE: N/A