



SPECIFICATIONS

|                 |            |
|-----------------|------------|
| Filter type     | C          |
| Capacitance     | 470 pF±20% |
| Working voltage | 100 V      |
| Current rating  | 6,5 A      |

Minimum insertion loss

| FREQUENCY (MHz) | ATTENUATION (dB) |
|-----------------|------------------|
| 5               | -                |
| 10              | 1                |
| 50              | 10               |
| 100             | 15               |
| 500             | 35               |
| 1000            | 32               |

Note: Jack-screws are not pre-mounted to allow mounting from any ends

|       |          |      |                               |          |      |   |   |                      |
|-------|----------|------|-------------------------------|----------|------|---|---|----------------------|
|       |          |      |                               | Dot.     | Name | <br>All Dim. in mm<br>Orig. Size DIN A 4 | Male / Female D-Sub<br>filter adapter,<br>9 poles, 470 pF | Maßstab/<br>Scale    |
|       |          |      | Detail.                       | 03/09/07 | JS   |   |   | 1,5:1                |
|       |          |      | Insp.                         |          |      |   |   |                      |
| 34901 | 01/04/08 | BB   | Stand.                        |          |      |   | TB 09 64 100 7220   | Blatt/ Page<br>1 / 1 |
| 34894 | 12/03/08 | PK   |                               |          |      |   |   |                      |
|       | 03/09/07 | JS   |                               |          |      |   |   |                      |
| Mod.  | Dot.     | Name | HARTING EURL<br>F-95972 Paris |          |      |    | Sub.  |                      |