


more than you expect



PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE 1-4	@20°C	2.15 ohms max.
D.C. RESISTANCE 2-3	@20°C	0.050 ohms max.
D.C. RESISTANCE 6-10	@20°C	0.14 ohms max.
INDUCTANCE 1-4	66kHz, 100mVAC, Ls	1.55mH ±10%
LEAKAGE INDUCTANCE 1-4	tie(2+3, 6+10), 100kHz, 100mVAC, Ls	25.0uH typ., 50.0uH max.
DIELECTRIC RATING 4-10	tie(1+3), 3750VAC, 1 second	3000VAC, 1 minute
URNS RATIO	(4-1):(10-6)	7.142:1, ±1%
URNS RATIO	(4-1):(3-2)	7.692:1, ±1%
RESONANT FREQUENCY	-	500kHz min.

REV.	DATE	Packaging Specifications Method: Tray PKG-0887 www.wg-online.com/midcom	 CONVENTION PLACEMENT
6B	12/12		
6A	2/09		

SEE REVISION SHEET FOR REVISION LEVEL

Tolerances unless otherwise specified:
Angles: $\pm 1^\circ$ Decimals: $\pm .005$ [.13]
Fractions: $\pm 1/64$ Footprint: $\pm .005$ [.13]
This drawing is dual dimensioned. Dimensions
in brackets are in millimeters.

eiSos p/n: 750871032

SPECIFICATION SHEET 1 OF 1