

DPAD1, DPAD2, DPAD5, DPAD10

Dual Pico-Amp Diode

- High Impedance Protection Circuits

Absolute maximum ratings at $T_A = 25^{\circ}\text{C}$
Continuous Forward Gate Current 50 mA
Storage Temperature Range -55°C to $+125^{\circ}\text{C}$

At 25°C free air temperature: Electrical Characteristics		DPAD1			DPAD2			Process NJ01	
		Min	Typ	Max	Min	Typ	Max	Unit	Test Conditions
Reverse Current	I_R			- 1			- 2	pA	$V_R = -20\text{V}$
Breakdown Reverse Voltage	BV_R	- 45			- 45			V	$I_R = -1\text{ }\mu\text{A}$
Forward Voltage Drop	V_F		0.8	1.5		0.8	1.5	V	$I_F = 5\text{ mA}$
Capacitance	C_R			0.8			0.8	pF	$V_R = -5\text{ V}$ $f = 1\text{ MHz}$
Differential Capacitance	$ C_{R1} - C_{R2} $			0.2			0.2	pF	$V_{R1} = V_{R2} = -5\text{ V}$ $f = 1\text{ MHz}$

At 25°C free air temperature: Electrical Characteristics		DPAD5			DPAD10			Process NJ01	
		Min	Typ	Max	Min	Typ	Max	Unit	Test Conditions
Reverse Current	I_R			- 5			- 10	pA	$V_R = -20\text{V}$
Breakdown Reverse Voltage	BV_R	- 45			- 45			V	$I_R = -1\text{ }\mu\text{A}$
Forward Voltage Drop	V_F		0.8	1.5		0.8	1.5	V	$I_F = 5\text{ mA}$
Capacitance	C_R			0.8			2.0	pF	$V_R = -5\text{ V}$ $f = 1\text{ MHz}$
Differential Capacitance	$ C_{R1} - C_{R2} $		0.2			0.2		pF	$V_{R1} = V_{R2} = -5\text{ V}$ $f = 1\text{ MHz}$

TO-72 Package
Dimensions in Inches (mm)
Pin Configuration
1 Cathode 1, 2 Anode 1,
3 Cathode 2, 4 Anode 2

