

Г	1			2			3		4	
	BOM of cable kits 10087038									
	Components Name	Upper Cover	Lower cover	Shroud housing with ESD spring	Terminal Block Assembly	Cable Clamp	Screw lock with Board connector	Screw lock to cover & clamp		
A	Q'TY/ Kits	1	1	1	4	1	2	4		
vight Fcl.	 Notes: 1. This product meets euror and other country regular in GS-22-008. 2. The product is not intent to a manufacturing sold 3. Material: Die casting cover: Zn all pure tin platingShroud h Terminal block housing: Terminal: Copper alloy a according to Telcordia O ESD spring: Steel stainless 4. The cable must be flexit under the line as below after cable assembled. 5. Product specification GS Application specification: Packaging specification 	ations as described ded to be exposed ler process. loy with Cu; Nickel ousing: Black PBT Black PBT 30% Gf and performance CO. ess. ole to be bent draft shown S-12-562 I: GS-20-114	& 30% GF. F. Screw lock v Shroud h	Cable Clar Screw with board Connector ousing with ESD sprin			SCALE 1.50	Lower Cover	-Upper Cover	-Screw
Cop	spec ref tolerance std	*		dr Junon Hua			projection	MM	size A4	scale 1.000
				eng De-Feng C chr Abin Yu	tin 2011/08/2 2011/08/2				ecn no	ELX-DG-005300-2
D			SE SPECIFIED	appr Pei-Ming Z	heng 2011/08/3	30 produ	ict family	-	rel level	Released
	surface -		0.X ±0.3 0.XX ±0.15 0.XXX ±0.05	FCj	96 Pos (≝ _{E1T1}	Cable Conne	ector Kits	ou gwb	10087038	rev C
		angular	0° ±3 °	www.fci.com	cat. no.		- Produ	uct - Customer Drw	si	heet 2 of 2
	ProE File - REV C - 2009-06-09			2			3 PDS	Rev :C STA	TUS:Released	Printed: Sep 02, 2