Data Sheet

Coaxial PCB Connector 82_QMA-S50-0-2/111_N

Description

Straight PCB jack

Interface Standards QMA QLF compliant

Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	6 GHz	
Mechanical Data		
Board mounting type	surface mount	
Weight	0.0012 kg	
Environmental Data		
Operating temperature	-40 °C to 85 °C	
2011/65/EU (RoHS - including	compliant	
2015/863 and 2017/2102)		

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00012672	
Catalogue drawing	DCA-00012674	
Mounting hole	DOU-00012675	

Ordering Information

Bulk 100 pcs package

82_QMA-S50-0-2/111_NH

Remarks

PCB connector with stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.



HUBER+SUHNER

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER: 82_QMA-S50-0-2/111_NH