


### High Temperature Polyetheretherketone (PEEK) Pan-Ty® Cable Ties and Mounts

PEEK Cable Ties and mounts are ideal for use in high temperature and harsh chemical environments. PEEK is a dimensionally stable material that offers an excellent tensile rating with an operating temperature up to 500°F (260°C). It is halogen free and has a UL94V-0 flammability rating, generating low smoke and toxicity upon burn, contributing to improved workplace safety. It has excellent chemical resistance to almost all organic and inorganic chemicals and is extremely resistant to high levels of gamma radiation for a long-term bundling solution. PEEK cable ties and mounts can be used in a broad range of applications and environments including Oil and Gas, Automotive and Aerospace.



#### Key Features

#### Benefits

##### Material

<b>High Temperature Polyetheretherketone (PEEK) material</b>	Operating temperature range up to 500°F (260°C); maintains good tensile strength in high temperature environments
<b>Halogen-free material UL94V-0 flammability rating</b>	Emits very low smoke and gas upon burn; does not easily ignite when exposed to a flame source; safe material to use in enclosed spaces
<b>Chemical resistant material</b>	Withstands attack from most organic and inorganic chemicals; able to be used in harsh chemical environments, providing a long-term bundling solution
<b>Gamma radiation resistant material</b>	Maintains mechanical properties when exposed to high levels of gamma radiation; maintains tensile properties, providing longer useful life
<b>Good electrical isolation properties</b>	Non-metallic material provides an alternative to conductive fasteners; safe to use where a non-conductive material is specified and/or required
<b>Low water absorption</b>	Non-hygroscopic material provides excellent moisture resistance; won't absorb water in humid/steam environments; maintains dimensional stability and tensile strength

##### Cable Tie

<b>Cable tie design</b>	Threads easily and installs quickly compared to lacing cord, which requires time consuming, hand-tied knots that can lead to repetitive strain injuries
<b>Curved tip – applicable sizes</b>	Easy to pick up from flat surfaces; allows faster threading

##### Mount

<b>Mount cradle design</b>	Provides maximum stability for the cable bundle
<b>Low profile design</b>	Keeps bundle close to mounting surface where overhead space is limited

##### Technical Information

<b>UL flammability</b>	UL 94V-0
<b>Oxygen index</b>	35
<b>Radiation resistance</b>	1 x 10 <sup>9</sup> Rads
<b>Continuous use temperature</b>	-76° – 500°F (-60° – 260°C)
<b>Halogen free</b>	Yes
<b>RoHS compliant</b>	Yes

# High Temperature Polyetheretherketone (PEEK) Pan-Ty® Cable Ties and Mounts

## Applications

Applications for PEEK product include, but are not limited to, the following:

- Drilling down-hole electronics
- Nuclear power plants
- Vacuum ovens for optics
- Commercial cooking equipment
- High temperature lighting
- Industrial ovens
- Transformers and transducers
- Wire harnesses for harsh environments
- Chemical manufacturing
- Transportation


## Ordering Information

### Cable Ties

Part Number	Length In. (mm)	Width In. (mm)	Thickness In. (mm)	Head Height In. (mm)	Head Width In. (mm)	Max. Bundle Diameter In. (mm)	Min. Loop Tensile Strength Lbs. (N)	Recommended Tools	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>Miniature Cross Section</b>										
<b>NEW!</b> PLT1M-C71	3.9 (99)	.098 (2.5)	.048 (1.2)	.131 (3.3)	.188 (4.8)	.87 (22)	35 (156)	GTS, GTSL, PTS	100	1000
<b>NEW!</b> PLT1.5M-C71	5.8 (147)					1.38 (35)			100	1000
<b>Standard Cross Section (Straight Tip)</b>										
PLT2S-C71	7.4 (188)	0.190 (4.8)	0.055 (1.4)	0.240 (6.1)	0.320 (8.1)	1.88 (48)	150 (668)	GTS, GTSL, GTH, PTS, PTH	100	1000

### Cable Tie Mounts

Part Number	Used With Cable Ties	A Width In. (mm)	B Width In. (mm)	C Height In. (mm)	Counterbore Diameter In. (mm)	Mounting Method	Std. Pkg. Qty.*	Std. Ctn. Qty.*
<b>NEW!</b> TM2S8-C71	Min., Std.	.636 (16.2)	.427 (10.8)	.278 (7.1)	.335 (8.5)	#8 (M4) screw	100	100



## Related products



Part Numbers	Used with PEEK Cable Ties	Description	Std. Pkg. Qty.
<b>Tool Controlled Tension and Cut-Off Tools</b>			
GTS, GTSL, GS2B	Miniature, Standard	Tool controlled tension tools consistently provide flush tie cut-offs to speed installation.	1
GS4H, GTH, GS4EH	Standard		1

\*Order number of pieces required, in multiples of standard package quantity.

### WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA  
Markham, Ontario  
cs-cdn@panduit.com  
Phone: 800.777.3300

PANDUIT EUROPE LTD.  
London, UK  
cs-emea@panduit.com  
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.  
Republic of Singapore  
cs-ap@panduit.com  
Phone: 65.6305.7575

PANDUIT JAPAN  
Tokyo, Japan  
cs-japan@panduit.com  
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA  
Jalisco, Mexico  
cs-la@panduit.com  
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.  
Victoria, Australia  
cs-aus@panduit.com  
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to [www.panduit.com/warranty](http://www.panduit.com/warranty)

For more information

Visit us at [www.panduit.com](http://www.panduit.com)

Contact Customer Service by email: [cs@panduit.com](mailto:cs@panduit.com)  
or by phone: 800-777-3300 and reference CTCB41

**PANDUIT**®

©2010 Panduit Corp.  
ALL RIGHTS RESERVED.  
Product Bulletin Number **WW-CTCB41**  
Replaces SA-CTCB22  
4/2010