

EDS8PS & EDS16PS

Hybrid Ethernet Terminal & MultiPort Device Servers

REMOTELY MONITOR, MANAGE AND CONTROL YOUR DEVICES

The EDS8PS and EDS16PS are unique, hybrid Ethernet terminal/multiport device servers which allow remote access to and management of virtually any IT/networking equipment or edge device like medical equipment, POS terminals or security equipment.

Featuring Lantronix' powerful Evolution OS™, EDS delivers an unprecedented level of intelligence and safety. With AES, SSH and SSL built in, EDS provides enterprise-level security allowing safe remote access and management from practically anywhere.

With no special software required, setup is a breeze with our Windows-based DeviceInstaller™, which can be used locally or remotely using Telnet, a web browser or XML.

Evolution OS provides 'data-center grade' protection so each networked device carries the same level of security as corporate data center equipment and provides robust defenses to hostile Internet attacks.

A "Cisco-like" command line interface (CLI) simplifies configuration and control, making it easier to integrate edge devices or data center equipment into the network.

Included, Lantronix' proprietary Com Port Redirector™ virtualization software allows existing applications to work with the EDS with no code modifications.



- + Quickly connect any device with a serial port to the network using robust SSH or SSL enterprise-level security
- + Easily customize and enhance the EDS for your unique application with Evolution OS™
- + Simple device set-up, configuration and monitoring with powerful, industry-standard management tools (Web, CLI, XML, SNMP)
- + Sleek design, desktop or wall-mount, perfect for medical or other high visibility installations

FEATURES

- + **32-bit Intel X-Scale IXP420 processor at 266 MHz**
- + **On –board memory**
 - 8MB Flash
 - 64 MB SDRAM
 - 2 KB Program Cache/32K instruction and data cache
- + **Serial Interface**
 - Software selectable data rates from 300 to 230K Baud
 - Characters: 7 or 8 data bits
 - Parity: Odd, Even, None
 - Stop Bits: 1 or 2
 - Modem Control Signals: CTS, RTS, DTR, DCD
 - Flow Control: XON/XOFF (software), CTS/RTS (hardware), None
- + **Network Interface**
 - 10BaseT and 100Base-TX Link
 - 8 or 16 ports, RJ45 software selectable serial ports
 - Protocols: HTTP, HTTPS, FTP, TFTP, Telnet, TCP, UDP, LPD, DHCP, SSHv2, SSLv3, SNMP v2, Auto IP, RSS, ARP, ICMP, SYSLOG, AES, SMTP, DNS, BOOTP
- + **Security**
 - SSL v3, SSH v2
 - MD5, SHA-1
 - 3DES encryption
 - ARC 4 128-bit encryption
 - Password protections
 - IP address filtering
- + **Software**
 - Windows 98/ME/NT/2000/Vista-Based DeviceInstaller[™]
 - ComPort Redirector[™] and related utilities
 - Secure ComPort Redirector
- + **Management**
 - Internal web server, SNMP v2, Serial Login, Telnet SSH login, XML
 - Upgradeable FW via the Web Manager, FTP or serial port
 - Storage capacity 6 MB
- + **Environmental**
 - Operating: 0° to 55° C (32° to 131° F)
 - Storage: -40° to 70° C (-40° to 151° F)
 - Relative Humidity: 5 to 95%, non-condensing
- + **Power**
 - 100-240VAC, 50 to 60 Hz IEC-type cord
 - 20 Watts

+ Dimensions

EDS8 PS

- Length: 12.8cm (5.02 in.)
- Width: 22.7cm (8.92 in.)
- Height: 4.3cm (1.7 in.)
- Weight: 0.499Kg (1.1lbs)

EDS16PS

- Length: 12.8cm (5.02 in.)
- Width: 22.7cm (8.92 in.)
- Height: 6cm (2.36 in.)
- Weight: 0.616Kg (1.36lbs)

+ Regulatory Approvals

- FCC Part 15, Subpart B, Class A
- EN55022, Class A
- EN55022 and EN55024
- EN61000-4-2, EN6100-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-6, EN61000-4-11, EN61000-4-11
- ICES-003 Issue 4
- AS/NZS CISPR22, VCCI
- CSA C22.2 No. 60950-1-3
- UL 60950-1, EN60950-1 (Eu)
- CE, C-Tick

+ 2-year limited Warranty

ORDERING INFORMATION

+ Part Number

EDS008PS-02

EDS016PS-02

+ Description

EDS8PS multi-port, secure device server; 8-port, 100-240 VAC**EDS16PS** multi-port, secure device server; 16-port, 100-240 VAC

+ Accessories

200.2066A
200.2067A
200.2069A
200.2070A
200.2071
200.2072
200.2073
200.2074
500-153
ADP010104-01
200.0062
200.0063
200.0064
200.0065

RJ45 to DB25M cable adapter (DTE Device)
RJ45 to DB25F cable adapter (DTE Device)
RJ45 to DB9M cable adapter (DTE Device)
RJ45 to DB9F cable adapter (DTE Device)
RJ45 to DB9M cable adapter (DCE Device)
RJ45 to DB9F cable adapter (DCE Device)
RJ45 to DB25M cable adapter (DCE Device)
RJ45 to DB25F cable adapter (DCE Device)
Cable; RJ45 Loopback Adapter
Cable; rolled serial adapter, 0.1m (0.33 ft)
Cable; RJ45, 2 m (6.6 ft)
Cable; RJ45, 5 m (16.4 ft)
Cable; RJ45, 10 m (32.8 ft)
Cable; RJ45, 15 m (49.2 ft)

LANTRONIX[®]

CORPORATE HEADQUARTERS

15353 Barranca Parkway | Irvine | CA 92618 | USA | t: 800.422.7055 | f: 949.450.7232 | www.lantronix.com

©2009, Lantronix, Inc. Lantronix is a registered trademark, and DeviceInstaller, Evolution OS and Com Port Redirector are trademarks of Lantronix, Inc. All other trademarks are the property of their respective owners. Specifications subject to change without notice. All rights reserved.

910-548 02/09