



### Main

|                           |                                                                           |
|---------------------------|---------------------------------------------------------------------------|
| Product or component type | Pilot light                                                               |
| Lens type                 | Fresnel plastic                                                           |
| Light block supply        | Via transformer (f = 50/60 Hz)<br>Via integral transformer (f = 50/60 Hz) |

### Complementary

|                              |                  |
|------------------------------|------------------|
| Bezel material               | Plastic          |
| Mounting diameter            | 1.18 in (30 mm)  |
| Shape of signaling unit head | Round            |
| Cap/operator or lens colour  | Yellow           |
| Light source                 | Incandescent     |
| Bulb base                    | BA 9s            |
| [Us] rated supply voltage    | 110...120 V AC   |
| Operating position           | Any position     |
| Operating mode               | Normal           |
| CAD overall width            | 2.13 in (54 mm)  |
| CAD overall height           | 2.76 in (70 mm)  |
| CAD overall depth            | 1.65 in (42 mm)  |
| Device presentation          | Complete product |

### Environment

|                         |      |
|-------------------------|------|
| protective treatment    | TC   |
| IP degree of protection | IP66 |

### Offer Sustainability

|                                                                                                                                  |                                                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| 785901041184                                                                                                                     | 785901041184                                                                                                                     |
| Compliant - since 0921 - Schneider Electric declaration of conformity                                                            | Compliant - since 0921 - Schneider Electric declaration of conformity                                                            |
| Reference not containing SVHC above the threshold                                                                                | Reference not containing SVHC above the threshold                                                                                |
| WARNING: This product can expose you to chemicals including:                                                                     | WARNING: This product can expose you to chemicals including:                                                                     |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|