

IF4511

N-Channel Silicon Junction Field-Effect Transistor

• Audio Amplifier

Absolute maximum ratings at $T_A = 25^\circ\text{C}$

Reverse Gate Source & Reverse Gate Drain Voltage	- 20 V
Continuous Forward Gate Current	10 mA
Continuous Device Power Dissipation	300 mW
Power Derating	1.8 mW/°C
Storage Temperature Range	- 65°C to 200°C

At 25°C free air temperature:

Static Electrical Characteristics

		IF4511		Process NJ450H		
		Min	Max	Unit	Test Conditions	
Gate Source Breakdown Voltage	$V_{(BR)GSS}$	- 20		V	$I_G = -1\ \mu\text{A}, V_{DS} = \emptyset\text{V}$	
Gate Reverse Current	I_{GSS}		- 0.1	nA	$V_{GS} = -30\text{V}, V_{DS} = \emptyset\text{V}$	
Gate Source Cutoff Voltage	$V_{GS(OFF)}$	- 0.35	- 1.5	V	$V_{DS} = 15\text{V}, I_D = 0.5\ \text{nA}$	
Drain Saturation Current (Pulsed)	I_{DSS}	5		mA	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$	

Dynamic Electrical Characteristics

Common Source Forward Transconductance	g_{fs}	15		mS	$V_{DS} = 15\text{V}, I_D = 5\ \text{mA}$	$f = 1\ \text{kHz}$
Common Source Input Capacitance	C_{iss}		35	pF	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$	$f = 1\ \text{MHz}$
Common Source Reverse Transfer Capacitance	C_{rss}		8	pF	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$	$f = 1\ \text{MHz}$

Typ

Equivalent Short Circuit Input Noise Voltage	\bar{e}_N	1.5		nV/√Hz	$V_{DG} = 12\text{V}, V_{GS} = \emptyset\text{V}$	$f = 1\ \text{kHz}$
--	-------------	-----	--	--------	---	---------------------

TO-72 Package

Dimensions in Inches (mm)

Pin Configuration

1 Source, 2 Drain, 3 Gate, 4 Case