




Coding Spline
Working Temp: 125°C
Color: Red
Body: PA66/6 UL94-Vo
Application: Plug-in Connectors


POL-P


Cat. #	Length (mm)	Std. Pk.
POL-P	7.90	30/5

Used for parts:

PVXX-5.00, 5.08, 7.50
PHXX-5.00, 5.08, 7.50
PVPXX-5.00, 5.08, 7.50
PHPXX-5.00, 5.08, 7.50
PDSHXX-5.00, 5.08
PDSVXX-5.00, 5.08
PDVXX-5.00, 5.08
PDHXX-5.00, 5.08
PIXX-5.00, 5.08
PIPXX-5.00, 5.08
SFX-5.00, 5.08




Coding Spline
Working Temp: 125°C
Color: Red
Body: PA66/6 UL94-Vo
Application: Plug-in Connectors


POL-S


Cat. #	Length (mm)	Std. Pk.
POL-S	7.90	30/5

Used for parts:


SHXX-5.00, 5.08, 7.50
PVPXX-3.50, 3.81
PHPXX-3.50, 3.81
SVFXX-5.08
SVP-5.08




Jumpers, Adjacent
Working Temp: 125°C
Color: Green
Body: PA66/6 UL94-Vo
Application: Jumper Connection
Design: 5.08 Spacing Modular


PT5

Cat. #	Length (B) (mm)	Std. Pk.
PT5	10.16	100



Jumpers, Alternate
Working Temp: 125°C
Color: Green
Body: PA66/6 UL94-Vo
Application: Jumper Connection
Design: 10.16 Spacing Modular


PT10

Cat. #	Length (B) (mm)	Std. Pk.
PT10	10.16	100

