

WA SERIES
85°C 9mm~25mm Height

*Load Life : 85°C 2000 hours.


◆ SPECIFICATIONS

Items	Characteristics	
Category Temperature Range	-40~+85°C	-25~+85°C
Rated Voltage Range	6.3~250Vdc	350~450Vdc
Capacitance Tolerance	±20%(20°C, 120Hz)	
Leakage Current(MAX)	6.3~50Vdc	160~450Vdc
	I=0.01CV or 3µA whichever is greater. (After 2 minutes application of rated voltage)	CV≤1000
		CV>1000
	I=0.1CV+40µA (1minute) I=0.03CV+15µA (5minutes)	I=0.04CV+100µA (1minute) I=0.02CV+25µA (5minutes)
	I=Leakage Current(µA)	C=Capacitance(µF) V=Rated Voltage(Vdc)
Dissipation Factor(MAX) (tanδ)	Rated Voltage (Vdc)	6.3 10 16 25 35 50 160 200 250 350 400 450 (20°C, 120Hz)
	tanδ	0.26 0.22 0.18 0.16 0.14 0.12 0.20 0.20 0.20 0.20 0.20 0.20
	When capacitance is over 1000µF, tanδ shall be added 0.02 to the listed value with increase of every 1000µF.	
Endurance	After applying rated voltage with rated ripple current for 2000 hours at 85°C, the capacitors shall meet the following requirements.	
	Capacitance Change	Within ±25% of the initial value.
	Dissipation Factor	Not more than 200% of the specified value.
	Leakage Current	Not more than the specified value.
Low Temperature Stability Impedance Ratio(MAX)	Rated Voltage (Vdc)	6.3 10 16 25 35 50 160 200 250 350 400 450 (120Hz)
	Z(-25°C)/Z(20°C)	6 4 4 3 2 2 3 3 3 5 5 7
	Z(-40°C)/Z(20°C)	12 10 8 6 4 3 - - - - -

◆ MULTIPLIER FOR RIPPLE CURRENT

Frequency (Hz)	60(50)	120	500	1k	10k≤	
Coefficient	1.5~6.8µF	0.65	1.00	1.20	1.30	1.50
	10~68µF	0.80	1.00	1.20	1.30	1.50
	100~1000µF	0.80	1.00	1.10	1.15	1.20
	2200~10000µF	0.80	1.00	1.05	1.10	1.15

◆ OPTION

	Code
PET Sleeve	EFC

◆ PART NUMBER

□□□	WA	□□□□□	M	□□□	□□	D×L
Rated Voltage	Series	Capacitance	Capacitance Tolerance	Option	Lead Forming	Case Size

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Rubycon:

[10WA10000MEFC18X25](#) [10WA1000MEFC10X9](#) [10WA2200MEFC12.5X16](#) [10WA3300MEFC16X16](#)
[10WA4700MEFC16X20](#) [10WA470MEFC8X9](#) [6.3WA3300MEFC12.5X16](#) [6.3WA4700MEFC18X16](#)
[6.3WA470MEFC8X9](#) [6.3WA6800MEFC16X20](#) [6.3WA680MEFC8X9](#) [50WA2200MEFC18X25](#) [50WA470MEFC12.5X16](#)
[50WA680MEFC16X16](#) [6.3WA10000MEFC18X20](#) [6.3WA1000MEFC10X9](#) [6.3WA2200MEFC12.5X16](#)
[450WA2R2MEFC10X9](#) [450WA47MEFC18X25](#) [450WA6R8MEFC12.5X16](#) [50WA1000MEFC16X20](#)
[50WA100MEFC8X9](#) [50WA150MEFC10X9](#) [400WA4R7MEFC10X9](#) [400WA68MEFC18X25](#) [400WA6R8MEFC12.5X16](#)
[450WA10MEFC16X16](#) [450WA1R5MEFC8X9](#) [450WA22MEFC16X20](#) [35WA680MEFC12.5X16](#)
[400WA10MEFC12.5X16](#) [400WA22MEFC18X16](#) [400WA33MEFC16X20](#) [400WA3R3MEFC10X9](#)
[400WA47MEFC18X20](#) [35WA1000MEFC16X16](#) [35WA150MEFC8X9](#) [35WA2200MEFC18X20](#) [35WA220MEFC10X9](#)
[35WA3300MEFC18X25](#) [35WA330MEFC10X9](#) [350WA33MEFC18X16](#) [350WA3R3MEFC8X9](#) [350WA47MEFC16X20](#)
[350WA4R7MEFC10X9](#) [350WA68MEFC18X25](#) [350WA6R8MEFC12.5X16](#) [25WA680MEFC12.5X16](#)
[25WA2200MEFC16X20](#) [25WA220MEFC8X9](#) [25WA3300MEFC18X20](#) [350WA10MEFC12.5X16](#)
[350WA22MEFC16X16](#) [250WA10MEFC10X9](#) [250WA100MEFC18X20](#) [25WA1000MEFC12.5X16](#)
[25WA330MEFC10X9](#) [25WA4700MEFC18X25](#) [25WA470MEFC10X9](#) [250WA22MEFC12.5X16](#) [250WA33MEFC16X16](#)
[250WA47MEFC18X16](#) [250WA68MEFC16X20](#) [250WA6R8MEFC10X9](#) [250WA150MEFC18X25](#)
[200WA10MEFC10X9](#) [200WA150MEFC18X25](#) [200WA47MEFC16X16](#) [200WA4R7MEFC8X9](#) [200WA68MEFC18X16](#)
[200WA6R8MEFC8X9](#) [16WA330MEFC8X9](#) [16WA4700MEFC18X20](#) [16WA470MEFC8X9](#) [16WA6800MEFC18X25](#)
[16WA680MEFC10X9](#) [200WA100MEFC16X20](#) [160WA47MEFC12.5X16](#) [160WA4R7MEFC8X9](#) [160WA68MEFC16X16](#)
[160WA6R8MEFC8X9](#) [16WA2200MEFC16X16](#) [16WA3300MEFC16X20](#) [10WA6800MEFC18X20](#)
[160WA100MEFC16X20](#) [160WA10MEFC10X9](#) [160WA150MEFC18X20](#) [160WA220MEFC18X25](#)
[160WA33MEFC12.5X16](#)