

Patch cable - VS-FSDB-IP20SDA/981/5,0 SCO - 1420184

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Assembled USB cable, shielded, color: black, PVC outer sheath, USB mini-B/IP20 on USB type A/IP20, length: 5 m

Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 427 (PC-2011)
GTIN	 4 046356 548618
Custom tariff number	85444290
Country of origin	GERMANY

Technical data

Mechanical characteristics

Number of positions	4
Shielded	Yes
Insertion/withdrawal cycles	≥ 100
Cable structure	28AWG_TP + 20AWG_2C; USB
Length of cable	5 m
Ambient temperature (operation)	-25 °C ... 80 °C (cable, flexible installation)

Material data

Inflammability class according to UL 94	UL94-V0
Contact material	Cu alloy
Contact surface material	Ni/Au
Outer sheath, material	PVC
External sheath, color	black
Degree of protection	IP20

Electrical characteristics

Transmission characteristics (category)	USB 2.0
---	---------

Patch cable - VS-FSDB-IP20SDA/981/5,0 SCO - 1420184

Classifications

eclass

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27259205
eCl@ss 6.0	27269202
eCl@ss 7.0	27449203

etim


ETIM 4.0	EC001408
----------	----------

unspsc

UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501


Drawings

Schematic diagram



Pin assignment plug USB, type A

Dimensioned drawing



USB plug connector, type A, Standard