


## Transmissive Optical Sensor with Phototransistor Output

### Description

The TCST1030 and TCST1030L are transmissive sensors that include an infrared emitter and phototransistor, located face-to-face on the optical axes in a leaded package which blocks visible light. TCST1030L is the long lead version.



### Features

- Package type: Leaded
- Detector type: Phototransistor
- Dimensions:  
L 8.3 mm x W 4.7 mm x H 8.15 mm
- Gap: 3 mm
- Aperture: none
- Typical output current under test:  $I_C = 2.4 \text{ mA}$
- Daylight blocking filter
- Emitter wavelength 950 nm
- Lead (Pb)-free soldering released
- Lead (Pb)-free component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



19171

### Applications

- Optical switch
- Shaft encoder
- Detection of opaque material such as paper
- Detection of magnetic tapes

### Order Instructions

Part Number	Remarks	Minimum Order Quantity
TCST1030	3.4 mm lead length	5200 pcs, 65 pcs/tube
TCST1030L	16 mm lead length	2600 pcs, 65 pcs/tube

### Absolute Maximum Ratings

$T_{amb} = 25^\circ\text{C}$ , unless otherwise specified

### Coupler

Parameter	Test condition	Symbol	Value	Unit
Total power dissipation	$T_{amb} \leq 25^\circ\text{C}$	$P_{tot}$	250	mW
Operation temperature range		$T_{amb}$	- 25 to + 85	$^\circ\text{C}$
Storage temperature range		$T_{stg}$	- 25 to + 100	$^\circ\text{C}$
Soldering temperature	1.6 mm from case, $t \leq 10 \text{ s}$	$T_{sd}$	260	$^\circ\text{C}$

## Input (Emitter)

Parameter	Test condition	Symbol	Value	Unit
Reverse voltage		$V_R$	6	V
Forward current		$I_F$	60	mA
Forward surge current	$t_p \leq 10 \mu s$	$I_{FSM}$	3	A
Power dissipation	$T_{amb} \leq 25^\circ C$	$P_V$	100	mW
Junction temperature		$T_j$	100	$^\circ C$

## Output (Detector)

Parameter	Test condition	Symbol	Value	Unit
Collector emitter voltage		$V_{CEO}$	70	V
Emitter collector voltage		$V_{ECO}$	7	V
Collector current		$I_C$	100	mA
Power dissipation	$T_{amb} \leq 25^\circ C$	$P_V$	150	mW
Junction temperature		$T_j$	100	$^\circ C$

## Electrical Characteristics

$T_{amb} = 25^\circ C$ , unless otherwise specified

## Coupler

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Collector current	$V_{CE} = 5 V, I_F = 10 mA$	$I_C$	1.2	2.4		mA
Collector emitter saturation voltage	$I_F = 10 mA, I_C = 1 mA$	$V_{CEsat}$			0.8	V

## Input (Emitter)

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Forward voltage	$I_F = 60 mA$	$V_F$		1.25	1.5	V
Junction capacitance	$V_R = 0, f = 1 MHz$	$C_j$		50		pF

## Output (Detector)

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Collector emitter voltage	$I_C = 1 mA$	$V_{CEO}$	70			V
Emitter collector voltage	$I_E = 10 \mu A$	$V_{ECO}$	7			V
Collector dark current	$V_{CE} = 25 V, I_F = 0, E = 0$	$I_{CEO}$		10	100	nA

## Switching Characteristics

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Turn-on time	$I_C = 1 mA, V_{CE} = 5 V, R_L = 100 \Omega$ (see figure 1)	$t_{on}$		15.0		$\mu s$
Turn-off time	$I_C = 1 mA, V_{CE} = 5 V, R_L = 100 \Omega$ (see figure 1)	$t_{off}$		10.0		$\mu s$




Figure 1. Test Circuit for  $t_{on}$  and  $t_{off}$




Figure 3. Power Dissipation Limit vs. Ambient Temperature




Figure 2. Switching Times

## Typical Characteristics

$T_{amb} = 25^\circ\text{C}$ , unless otherwise specified




Figure 4. Forward Current vs. Forward Voltage




Figure 5. Relative Current Transfer Ratio vs. Ambient Temperature




Figure 6. Collector Dark Current vs. Ambient Temperature




Figure 9. Current Transfer Ratio vs. Forward Current




Figure 7. Collector Current vs. Forward Current




Figure 10. Turn on/off Time vs. Collector Current




Figure 8. Collector Current vs. Collector Emitter Voltage




Figure 11. Relative Collector Current vs. Displacement


Undimensioned conicity (taper) max. 0°30'

Optical axis


Reference plain

TFK 4 147  
TCST 1030


\* Tolerances related to reference plain




weight: ca. 0.25g



96 12074




## Tube Dimensions in mm



With stopper pins  
Tolerance:  $\pm 0.5\text{mm}$   
Length:  $575 \pm 1\text{mm}$   
All dimensions in mm

Drawing-No.: 9.700-5140.01-4  
Issue: 1; 25.02.00  
20253



With stopper pins  
Tolerance:  $\pm 0.5\text{mm}$   
Length:  $575 \pm 1\text{mm}$   
All dimensions in mm

Drawing-No.: 9.700-5205.01-4

Issue: 1; 25.02.00

20254





## **Ozone Depleting Substances Policy Statement**

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design  
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.