

TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

Magnetic Mount

PART NUMBER: ARMXXXXXMM



Features:

- Low profile, only 1.8" tall
- Up to 6-lead Configuration
 - LTE(2x) MIMO
 - WiFi(3x) MIMO-|2.4/5.x GHz
 - GPS/GNSS (1x)
- Frequency of Operation:
 - 698-960MHz,1710-2690MHz
 - 2400-2500MHz,5150-5925MHz
 - 1559-1606MHz

Applications:

- Telematics, Navigation
- First Responders(Police, Fire, Ambulance/EMS)
- Energy, Utility, Construction
- Fleet Management
- DSRC(Dedicated Short Range Communications)
- Available Configurations:
 - · Black, White
 - Magnetic mount
 - For direct mount seep/N: ARMXXXXXDM



Issue: 1842

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:



TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

Magnetic Mount

PART NUMBER: ARMXXXXXMM

This document covers all product variants of the following product family

Product	Total Cable Leads	LTE Cable Leads	WiFi Cable Leads	GPS Cable Leads	Housing Color	Mounting
ARM62311MM	6	2	3	1	Black	Magnetic Mount; Pull force: 100N, 22lbf min. (Tested on 3mm thick steel plate.)
ARM62312MM	6	2	3	1	wille	
ARM52211MM	5	2	2	1	Black	
ARM52212MM	5	2	2	1	White	
ARM42111MM	4	2	1	1	Black	
ARM42112MM	4	2	1	1	White	

Product Numbering

Vehicular Multiband Antenna with Direct Mount

(Part Number)













•	Product ID: ARMADILLO
	Total Number of Cable leads
0	Total Number of LTE Cable Leads
0	Total Number of WiFi Cable Leads
0	Total Number of GPS Cable Leads
•	The Color of the Plastic Housing 1=Black; 2= White
(Mounting: Magnetic Mount

	ARMXXXXXMM	CABLE	CABLE LENGTH	CONNECTOR
1	LTE-1 Cable Assy		5181 mm / 204" / 17 FT	SMA Male
2	WiFi-1 Cable Assy	LMR-195 *		RP-SMA Male
3	WiFi-3 Cable Assy	LIVIR-195		RP-SMA Male
4	WiFi-2 Cable Assy			RP-SMA Male
5	GPS Cable Assy	LMR-100 *		SMA Male
6	LTE-2 Cable Assy	LMR-195 *		SMA Male

^{*} or equivalent



In the effort to improve our products, we reserve the right to make changes judged to be necessary.

RóHS



TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

6.3dBi

Vertical

Magnetic Mount

PART NUMBER: ARMXXXXXMM

ELECTRICAL SPECIFICATIONS				
Frequency	698-960MHz, 1710-2690MHz			
	2400-2500MHz, 5150-5925MHz			
Nominal Impedance	$50~\Omega$			
VSWR*				
698-960MHz	<2.5			
1710-2690MHz	<2.5			
2400-2500MHz	<2.5			
5150-5925MHz	<2.5			
Isolation*				
698-960MHz, 1710-2690MHz	-8dB			
2400-2500MHz, 5150-5925MHz	-12dB			
Radiation Pattern	Omni			
Average Peak Gain**				
698-960MHz	4.6dBi			
1710-2690MHz	5dBi			
2400-2500MHz	4.1dBi			

5150-5925MHz

Polarization

^{*}Test on 500mm ground plane with 17ft(5.2m) LMR195 cable

^{**}Test on 500mm ground plane with 1ft(304.8) LMR195 cable



TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

Magnetic Mount

PART NUMBER: ARMXXXXXMM

ELECTRICAL SPECIFICATIONS

GPS Antenna

Frequency 1561.098±2.046MHz/

1575.42±1.023MHz/

1602.5625±4MHz

Nominal Impedance 50 Ω

VSWR <2

Gain (Radiating Element) 1 dBic±1 dB

Gain (LNA Gain) 30 dB± 2 dB

Polarization RHCP

Out of Band Rejection

698 MHz >70 dB

960 MHz >65 dB

1710 MHz >60 dB

2170 MHz >65 dB

2400 MHz >65 dB

2700 MHz >65 dB

Noise Figure <2.4 dB

Operating Voltage 3.3 – 5 Vdc

Current Consumption <15mA



TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

Magnetic Mount

PART NUMBER: ARMXXXXXMM

MECHANICAL SPECIFICATIONS

Overall Length 202.3mm X 88.5mm X 45mm

Weight 1.1 Kg

Antenna Color / Material

Connector type

Cable type

Cable length

Black or White
Refer to Page 2
Refer to Page 2
Refer to Page 2

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature $-40 \sim +85^{\circ}$ C Storage Temperature $-40 \sim +85^{\circ}$ C

Ingress Protection IP67
RoHS Compliant Yes

OTHER SPECIFICATIONS

Total cable assembly loss for 5.2m (17') LMR-195 @850MHz	2.1dB
Total cable assembly loss for 5.2m (17') LMR-100 @1575MHz	5.9dB
Total cable assembly loss for 5.2m (17') LMR-195 @1930MHz	3.2dB
Total cable assembly loss for 5.2m (17') LMR-195 @2450MHz	3.6dB
Total cable assembly loss for 5.2m (17') LMR-195 @2500MHz	3.7dB
Total cable assembly loss for 5.2m (17') LMR-195 @5350MHz	5.5dB




TECHNICAL DATA SHEET


Description: Vehicular Multiband Antenna with

Magnetic Mount

PART NUMBER: ARMXXXXXMM

MECHANICAL DRAWING








TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

Magnetic Mount

PART NUMBER: ARMXXXXXMM

MECHANICAL DRAWING



	ARMXXXXXMM	CABLE	CABLE LENGTH	CONNECTOR
1	LTE-1 Cable Assy		5181 mm / 204" /	SMA Male
2	WiFi-1 Cable Assy	LMR-195 *		RP-SMA Male
3	WiFi-3 Cable Assy	LIVIR-193		RP-SMA Male
4	WiFi-2 Cable Assy			RP-SMA Male
5	GPS Cable Assy	LMR-100 *	17 FT	SMA Male
6	LTE-2 Cable Assy	LMR-195 *		SMA Male

Issue: 1: * or equivale

KOHS



TECHNICAL DATA SHEET


Description: Vehicular Multiband Antenna with

Magnetic Mount

PART NUMBER: ARMXXXXXMM

TEST SETUP

Antenna tested on a Φ500mm ground plane.









TECHNICAL DATA SHEET


Description: Vehicular Multiband Antenna with

Magnetic Mount


PART NUMBER: ARMXXXXXMM

CHARTS

VSWR (LTE)



Isolation (LTE)



Note: Antenna tested with 5m cable on 500mm (dia) ground plane





TECHNICAL DATA SHEET


Description: Vehicular Multiband Antenna with

Magnetic Mount


PART NUMBER: ARMXXXXXMM

CHARTS

Radiation Efficiency (LTE)



Peak Gain (LTE)



Note: Antenna tested with 1ft(304.8mm) cable on 500mm (dia) ground plane

Issue: 1842

ROHS



TECHNICAL DATA SHEET


Description: Vehicular Multiband Antenna with

Magnetic Mount


PART NUMBER: ARMXXXXXMM

CHARTS

VSWR (WIFI)



Isolation (WIFI)



Note: Antenna tested with 5m cable on 500mm (dia) ground plane

Issue: 1842



TECHNICAL DATA SHEET


Description: Vehicular Multiband Antenna with

Magnetic Mount


PART NUMBER: ARMXXXXXMM

CHARTS

Radiation Efficiency (WIFI)



Peak Gain (WIFI)



Note: Antenna tested with 1ft(304.8mm) cable on 500mm (dia) ground plane



12




TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with


Magnetic Mount

PART NUMBER: ARMXXXXXMM

CHARTS



LTE1 XY plane radiation pattern



LTE2 XY plane radiation pattern




TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with


Magnetic Mount

PART NUMBER: ARMXXXXXMM

CHARTS



LTE1 ZX plane radiation pattern



LTE2 ZX plane radiation pattern






TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with


Magnetic Mount

PART NUMBER: ARMXXXXXMM

CHARTS



LTE1 YZ plane radiation pattern



LTE2 YZ plane radiation pattern




TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with


Magnetic Mount

PART NUMBER: ARMXXXXXMM

CHARTS



LTE1 XY plane radiation pattern



LTE2 XY plane radiation pattern




TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with


Magnetic Mount

PART NUMBER: ARMXXXXXMM

CHARTS



LTE1 ZX plane radiation pattern



LTE2 ZX plane radiation pattern




TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with


Magnetic Mount

PART NUMBER: ARMXXXXXMM

CHARTS



LTE1 YZ plane radiation pattern



LTE2 YZ plane radiation pattern






TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

Magnetic Mount


PART NUMBER: ARMXXXXXMM





WiFi1 XY plane radiation pattern

WiFi2 XY plane radiation pattern



WiFi3 XY plane radiation pattern





2400MHz

2450MHz

2500MHz

Avg (dBi) = -4.43 Peak (dBi) = -0.51 Avg -3 (deg) = 128

Avg (dBi) = -4.30 Peak (dBi) = -0.01 Avg -3 (deg) = 164

Avg (dBi) = -4.19 Peak (dBi) = 0.06 Avg -3 (deg) = 164




TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

Magnetic Mount

PART NUMBER: ARMXXXXXMM



WiFi1 ZX plane radiation pattern


Theta Angle (°)

2400MHz

-2450MHz --- 2500MH:

WiFi2 ZX plane radiation pattern

Theta Angle (°)



WiFi3 ZX plane radiation pattern





2400MHz -

-2450MHz --- 2500MH:




TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

Magnetic Mount


PART NUMBER: ARMXXXXXMM





WiFi1 YZ plane radiation pattern

WiFi2 YZ plane radiation pattern



WiFi3 YZ plane radiation pattern








TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

Magnetic Mount


PART NUMBER: ARMXXXXXMM





WiFi1 XY plane radiation pattern

WiFi2 XY plane radiation pattern



WiFi3 XY plane radiation pattern

5150MHz

5550MHz

5950MHz

Avg (dBi) = -2.90 Peak (dBi) = 2.86 Avg -3 (deg) = 80

Avg (dBi) = -4.24 Peak (dBi) = 2.14 Avg -3 (deg) = 56

Avg (dBi) = -2.16 Peak (dBi) = 4.64 Avg -3 (deg) = 92




TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with


Magnetic Mount

PART NUMBER: ARMXXXXXMM



WiFi1 ZX plane radiation pattern

WiFi2 ZX plane radiation pattern



WiFi3 ZX plane radiation pattern







TECHNICAL DATA SHEET


Description: Vehicular Multiband Antenna with

Magnetic Mount

Avg (dBi) = -7.08 Peak (dBi) = 4.51 Avg -3 (deg) = 19

5150MHz - 5550MHz - 5950MHz

PART NUMBER: ARMXXXXXMM



5950MHz Avg (dBi) = -5.87 Peak (dBi) = 4.20 Avg -3 (deg) = 0.5

- 5550MHz -

-5950MHz

5150MHz -

Theta Angle (°)

WiFi1 YZ plane radiation pattern

Theta Angle (°)


YZ Plane

-25

-30

ower (dBm)

WiFi2 YZ plane radiation pattern



WiFi3 YZ plane radiation pattern



TECHNICAL DATA SHEET

Description: Vehicular Multiband Antenna with

Magnetic Mount

PART NUMBER: ARMXXXXXMM

PACKAGING

Each antennas packed in Bubble Bag

6 bags of antennas (Total 6pcs) packed in a cardboard box

1 label on each box with quantity, part number, date code.