



VOLEX RESERVES THE RIGHT TO ALTER NON-CRITICAL DIMENSIONS WITHOUT NOTICE.

**NOTES:**

- 1) CORDAGE: 18/2 SPT-1, 105°C, BLACK
- 2) APPROVALS: UL/CSA WIRING HARNESS.
- 3) RATING: 1 AMP/250 VOLTS
- 4) FLAME RATING : VW1
- 5) CORDAGE DIMENSIONS: .110" X .220" REF.
- 6) CORD IS NOT POLARIZED, RIBBED LEAD WILL NOT ALWAYS BE IN SAME POSITION WITH REFERENCE TO THE CONNECTOR.
- 7) PACKAGING: 100 PIECES PER CARTON.
- 8) ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED.

CONNECTOR: PHX707 A  
 COLOR: BLACK

**CUD**

FORM IN71-07 REV.A

Indianapolis, IN

Conover, N.C.

Freemont, CA

Aguascalientes, MX

Tijuana, Mexico

Hermosillo, MX

Clinton, AR

Kanata, Canada

**Proprietary Notice:**

This document is the property of Volex Incorporated. The information contained herein is not to be disclosed to anyone without the express written consent of Volex Inc.

**MATERIAL:**  
 PLUG: PVC, BLACK  
 JACKET: PVC, BLACK

**FINISH:**

REV	SCALE: NDT TO SCALE	ECO:	ITEM DESCRIPTION	DESCRIPTION	DATE
1		N/A	C.U.D - NEW RELEASE	APPLANCE CORD FOR COOLING FAN	9/25/07

**TOLERANCE UNLESS OTHERWISE SPECIFIED**

.XXX ± .005

.XX ± .02

.X ± .03

FRACT. ± 1/32

ANGULAR ± 1/2°

**APPROVED**

STC

**DRAWN BY**

STC

**DATE:**

9/25/07

**PART NO.**

17905 10 B1