



Color L	Cat. 5e UTP AWG24 Solid Cable						
	Black	Black	Blue	Red	Green	Yellow	White
① 1M	17-103294	17-103304	17-103314	17-103324	17-103334	17-103344	17-103354
2M	17-101324	17-100654	17-100684	17-100714	17-100744	17-100774	17-100804
4M	17-101334	17-100664	17-100694	17-100724	17-100754	17-100784	17-100814
5M	17-101344	17-100674	17-100704	17-100734	17-100764	17-100794	17-100824
② 10M	17-103574	17-103584	17-103594	17-103604	17-103614	17-103624	17-103634

Notes: - Special cable lengths are available please contact factory; STP: Shielded Twisted Pair, UTP: Unshielded Twisted Pair

Notes:

1. Electrical:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
 - RJ45 Plug Operating Temperature: -40° C to +85° C
2. Materials and Finish:
 - RJ45 Plug Metal Shell: Copper Alloy, Nickel Plated
 - ③ - RJ45 Plug Plastic Housing: Clear Polycarbonate UL94 V-2
 - RJ45 Plug Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
 - RJ45 Modular Boot: PVC, Color: See P/N Table
 - Cable: See P/N Table
3. RoHS compliant

Directive 2002/95/EC RoHS Compliant

THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale: NTS	Dim. in Meter	
	Name		Title	Approval Date			Dimensional: Angles		Material: See Notes
						2008	Date	Name	
	e	1	Sep/16/2011	Vincent Ke		Draw.	Feb. 20	Vincent Ke	Title: RJ45 Cat. 5e Ethernet Patch Cord Standard to Standard RoHS Compliant
	d	1	Jul/06/2011	Vincent ke		Appd.	Feb. 20	J. Chaudry	
	c	1	Apr/08/2011	Vincent ke		Norm			
b	1	Dec/12/2008	Vincent ke		D-old				
a		original							
Rev.	Changes	Date	Name	CONEC®		Drawing No.: 39K1A375		DIN A3	
Part No.: SEE PART NUMBER ABOVE								Sheet 1/1	