Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



AX101170 Modular Connectors - Fusion Splice Protector

For more Information please call

1-800-Belden1

General Description:

Fusion Splice Protector, 900um to 250um, Blue

Usage (Overall)

Suitable Applications: FiberExpress Ultra Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data

Related Parts: Splice Trays And Splice Holder Kits

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

Height (in.) Width (in.) Length (in.) 0.088

Weight

0.001 lbs. Weight:

Packaging

Packaging: Individually packaged in a plastic bag, Shipped in cardboard box (50/box)

Mechanical Characteristics (Connectivity)

Installation Temperature Range: -5°C To +45°C

Applicable Specifications and Agency Compliance (Overall)

Suitability

Suitability - Indoor: Yes - Indoor

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: For additional information about this product visit our web site at http://www.belden.com.

Product Family

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX101170	25 EA	2.775 LB			FUSION SPLICE (25/PK)

Revision Number: 1 Revision Date: 09-15-2010

© 2015 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to

Antitogri Betider makes every reasonable entrit to ensure trief actuary at the time of this publication, information and specifications described freelin are subject to entrit of office of makes every reasonable entrit to entr

Page 1 of 1