



VOLEX RESERVES THE RIGHT TO ALTER NON-CRITICAL DIMENSIONS WITHOUT NOTICE.

NOTES:

- 1) CORDAGE: 18/2/SPT-1/105°C/BLACK
- 2) APPROVALS: UL/CSA WIRING HARNESS.
- 3) RATING: 1 AMP/250 VOLTS
- 4) FLAME RATING : VW1
- 5) CORDAGE DIMENSIONS: .110" X .220" REF.
- 6) CORD IS NOT POLARIZED. RIBBED LEAD WILL NOT ALWAYS BE IN SAME POSITION WITH REFERENCE TO THE CONNECTOR.
- 7) PACKAGING: 100 PIECES PER CARTON.
- 8) ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED.

REV	DESCRIPTION	DATE
1	C.U.D - NEW RELEASE	5/26/05



- Indianapolis, IN
- Conover, N.C.
- Freemont, CA
- Aguascalientes, MX
- Tijuana, Mexico
- Hermosillo, MX
- Clinton, AR
- Kanata, Canada

Proprietary Notice:

This document is the property of Volex Incorporated. The information contained herein is not to be disclosed to anyone without the express written consent of Volex Inc.

MATERIAL:
PLUG: PVC, CLEAR
JACKET: PVC, GRAY

FINISH:
JACKET: SMOOTH

SCALE:
NOT TO SCALE

ECD:
N/A

ITEM DESCRIPTION:
APLIANCE CORD FOR COOLING FAN

TOLERANCE UNLESS OTHERWISE SPECIFIED
.XXX ± .005
.XX ± .02
.X ± .03
FRACT. ± 1/32
ANGULAR ± 1/2°

APPROVED:
DRAWN BY: STC
DATE: 5/26/05

PART NO.: 17906 10 B1