


**Contact assignment:**

- 1) brown
- 2) white
- 3) blue
- 4) black
- 5) green-yellow



**Technical specification:**

Rated voltage: IEC 61076-2-101	4pos 5pos 250 V 60 V
Current rating: IEC 61076-2-101	4 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: DIN 40050-9	IP 69K, in mated condition
Temperature range: IEC 60664-1	-30°C ... +105°C
Mating cycles: IEC 60512-9a	>=100



**Materials:**

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	PP GF, UL 94
Sealing:	FPM
Socket housing:	1.4404, stainless steel
Grouting:	Polyurethane-resin, UL 94

**Installation specification:**

recommended torque:	1-1,2 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 17: 36-000230

Part no:	Description:	Pos	Length L:	Wire:
43-01018	SAL - FB - 12 - FK4 - 0,5	4	0,5m	AWG 24 PVC, UL
43-xxxxx	SAL - FB - 12 - FK4 - ...	4	x	
43-01019	SAL - FB - 12 - FK5 - 0,5	5	0,5m	
43-xxxxx	SAL - FB - 12 - FK5 - ...	5	x	

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: b 12.04.11 fro Ä3914 Data sheet revised, technical specification changed, Sleeve side B removed	 dim. in mm	title: <b>Female socket M12x1 with wire, frontmounting, FB</b>								
	tolerance of wire: L ≤ 0,5m: L + 20mm L > 0,5m: L + 4%				<table border="1"> <tr> <td></td> <td>date</td> <td>name</td> </tr> <tr> <td>drawn</td> <td>20.02.07</td> <td>Fromm</td> </tr> <tr> <td>appd.</td> <td>06.03.07</td> <td>Mankopf</td> </tr> </table>		date	name	drawn	20.02.07	Fromm
		date	name								
	drawn	20.02.07	Fromm								
appd.	06.03.07	Mankopf									
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH		dwg no: <div style="text-align: center; font-size: 1.2em; font-weight: bold;">43K1A290</div>									
		part no:									