



# Protect It! Surge Protector with 6 Swivel Outlets, Direct Plug-In, 1200 Joules, Coax/Tel/Modem Protection

## MODEL NUMBER: HTSWIVEL6











#### **Highlights**

- 6 rotatable outlets
- · Direct plug-in design
- 1200 joule rating
- 1 line tel/modem and 1-line gold coax (2.2GHz bandwidth) protection
- \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

# Package Includes

- HTSWIVEL6 Surge Suppressor
- Instruction manual with warranty information
- 6 ft. gold coaxial cable
- 6 ft. phone cord

### Description

Tripp Lite's HTSWIVEL6 Home/Business Theater Surge Suppressor provides high-performance protection--1200 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. 6 outlets, 1-line coaxial protection and 1-line tel/modem protection safeguard an entire home/business theater system. \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only). Includes two diagnostic LEDs, 6 ft. gold coaxial cable and 6 ft. phone cord.

#### **Features**

- 6 rotatable outlets allow for easier plug connection and removal
- 1200 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- 1 set of surge-protected Type F gold coaxial connectors (with included 6 ft. coaxial cable) safeguard components on cable, satellite or antenna line (2.2GHz bandwidth)
- 1 set of surge-protected tel/modem connectors (with included 6 ft. phone cord) safeguard personal video recorders (PVRs) on a single dial-up line
- 2 diagnostic LEDs alert user to protection and grounding status
- High-impact plastic housing (black) stands up to the most demanding environments
- Direct plug-in design converts two outlets into six by pluggin into any wall outlet
- \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

# **Specifications**

ОИТРИТ		
Frequency Compatibility	60 Hz	





Output Receptacles	(6) 5-15R		
Circuit Breaker (amps)	15		
Outlet Orientation	Rotatable		
INPUT			
Nominal Input Voltage(s) Supported	120V AC		
Recommended Electrical Service	120V (110-125V)		
Input Connection Type	NEMA 5-15P		
Input Cord Length (ft.)	0		
Input Cord Length (m)	Direct plug-in		
Input Cord Length Details	Direct Plug-In		
Voltage Compatibility (VAC)	120		
Maximum Surge Amps	60000		
USER INTERFACE, ALERTS & CONTROLS			
Diagnostic LED Details	Built-in LEDs confirm suppressor "protected" (green) and "grounded" (red) status		
SURGE / NOISE SUPPRESSION			
AC Suppression Joule Rating	1200		
AC Suppression Response Time	< 1 ns		
Protection Modes	Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression		
Clamping Voltage (RMS)	150		
UL1449 Let Through Rating	400, 500, 500		
EMI / RFI Filtering	Up to 20 dB		
DATALINE SURGE SUPPRESSION			
Telephone/DSL Protection	Yes		
Telephone/DSL Protection Details	1 line		
Cable (Coax) Protection	Yes		
Cable (Coax) Protection Details	1 line		
Network (Ethernet) Protection	No		
PHYSICAL			
Shipping Dimensions (hwd / in.)	8.6 x 5.8 x 2.38		
Shipping Dimensions (hwd / cm)	21.84 x 14.73 x 6.05		
Shipping Weight (lbs.)	1.0		





Shipping Weight (kg)	0.45			
Unit Dimensions (hwd / in.)	6.25 x 4 x 2.25			
Unit Dimensions (hwd / cm)	15.88 x 10.16 x 5.72			
Unit Weight (lbs.)	0.6			
Unit Weight (kg)	0.27			
Material of Construction	Plastic			
Receptacle Color	Black			
Outlets Measurement (Center to Center)	29mm			
Metal Case	No			
SPECIAL FEATURES				
Right-Angle Plug	No			
CERTIFICATIONS				
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition			
cUL / CSA (Canada)	cUL			
Approvals	RoHS			
WARRANTY				
Product Warranty Period (Worldwide)	Lifetime limited warranty			
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$50,000 Ultimate Lifetime Insurance			

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies