

8520 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

 For more Information
 please call

1-800-Belden1

**Description:**

Tinned copper, PVC insulation, medium wall. The extruded PVC insulation is flame and ozone resistant. Inert to most chemicals, oils, and solvents. Covers single cond., PVC insulated hook-up wire for internal wiring of electrical and electronic equipment.

Physical Characteristics (Overall)**Conductor****AWG:**

# Conductors	AWG	Stranding	Conductor Material
1	14	41x30	TC - Tinned Copper

Insulation**Insulation Material:**

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.4572

Overall Insulation**Overall Cabling**

Overall Nominal Diameter: 2.819 mm

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	MIL-W-76C
MIL Spec Rating:	1000 V, 80°C

Plenum/Non-Plenum

Plenum (Y/N): No

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8520 001100	30 MT	0.771 KG	BROWN		14 STR PVC BRN
8520 0011000	305 MT	7.711 KG	BROWN	P	14 STR PVC BRN
8520 002100	30 MT	0.771 KG	RED		14 STR PVC RED
8520 0021000	305 MT	7.711 KG	RED	P	14 STR PVC RED

METRIC MEASUREMENT VERSION

8520 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

8520 003100	30 MT	0.771 KG	ORANGE		14 STR PVC ORG
8520 0031000	305 MT	7.711 KG	ORANGE	P	14 STR PVC ORG
8520 005100	30 MT	0.771 KG	GREEN, DARK		14 STR PVC GRN
8520 0051000	305 MT	7.711 KG	GREEN, DARK	P	14 STR PVC GRN
8520 006100	30 MT	0.771 KG	BLUE, LIGHT		14 STR PVC LBLU
8520 0061000	305 MT	7.711 KG	BLUE, LIGHT	P	14 STR PVC LBLU
8520 0081000	305 MT	7.711 KG	GRAY	P	14 STR PVC GRY
8520 009100	30 MT	0.771 KG	WHITE		14 STR PVC WHT
8520 0091000	305 MT	7.711 KG	WHITE	P	14 STR PVC WHT
8520 010100	30 MT	0.771 KG	BLACK		14 STR PVC BLK
8520 0101000	305 MT	7.711 KG	BLACK	P	14 STR PVC BLK
8520 013100	30 MT	0.771 KG	BLUE, DARK		14 STR PVC DBLU
8520 0181000	305 MT	8.165 KG	WHITE/BLUE	A	14 STR PVC WHT/BLU

Notes:

A = STOCKED STRIPE COLORS.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 1 Revision Date: 05-14-2007

© 2011 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.