THIS IS ISSUED IN STRICT CONFIDENCE **REVISIONS** THAT IT IS NOT USED AS A BASIS FOR MANUFACTURE OR SALE AND THAT IT REV. **DESCRIPTIONS** DATE **APPROVED** IS NOT COPIED, REPRINTED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY OR IN PART WITHOUT THE CLASS A RELEASED 5/13/08 PRIOR WRITTEN CONSENT OF CAL TEST **ELECTRONICS. INC.** 1. SPECIAL FUSE HOLDER ASSEMBLY w/ ALLIGATOR CLIP ADAPTER. FUSE HOLDER HAS 4 mm SHEATHED BANANA JACK. 2. SPECIFICATIONS: INSULATORS: POLYAMIDE (NYLON). CONTACT: BRASS, NICKEL PLATED. BANANA PLUG CONTACT: BeCu ALLOY, NICKEL PLATED. - 3.18 – 3. RATING: [PROBE SHOWN OPEN] VOLTAGE: 1,000V CATIII P2 (IEC 61010-031) CURRENT: FUSE RATING: 0.5 A. TEMPERATURE: -20° C TO +80° C. 4.\ FUSE: 6x32 mm CERAMIC FS, 50k A I.R. Ø 1.02 CAL TEST FULLY INSULATED ALLIGATOR CLIPS SNAP-FIT INTO ADAPTER. (ONCE INSTALLED, CLIP CANNOT BE REMOVED.) 6. IMPORTANT - ASSEMBLY NOT TO USED AS A STAND ALONE ASSEMBLY. 5.48 7. MODEL IS ROHS COMPLIANT. PART NUMBER CT3211Sp-# ∠ 4 mm BANANA PLUG FUSE HOLDER (-# COLORS) - COLOR: 0 - BLACK 2 - RED SPECIAL ALLIGATOR CLIP 4 - YFIIOW ADAPTER (GREY) 5 - GRFFN 6 - BLUE CONTRACT NO. UNLESS OTHERWISE SPECIFIED THIRD ANGLE PROJECTION Cal Test Electronics 22820 Savi Ranch Parkway Yorba Linda, CA 92887-4610 **DIMENSIONS ARE IN INCHES** TOLERANCES ARE: FRACTIONS DECIMALS ± 1/32 .XX ± .02 **APPROVALS** DATE .XXX ±.005 TITLE DO NOT SCALE DRAWING FUSED PROBE ASSEMBLY, DRAWN 5/13/08 WDH SPECIAL ADAPT., 1000 V 0.5 A MATERIAL CHECKED ENGR. FINISH SIZE CAGE CODE DWG. NO. REV. P321100 43F45 DESIGN ACTIVITY **NEXT ASSY** USED ON 1 OF 1 APPLICATION SCALE 1:1 P3211Sp_r00.pdf SHEET