

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

ALL RIGHTS RESERVED.

LOC
J

DIST

REVISIONS



変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
A3	REVISED	FJ00-2017-00	21DEC00	N.Y	N.S
B	REVISED	ECR-06-024409	13NOV06	SK	SI
BI	REVISED	ECR-12-019260	08NOV12	TS	KB

1. INSTRUCTION SHEET ; 411-5919
2. DOUBLE LOCK SHOULD BE SET TO THE PRE-ASSEMBLY POSITION WITHIN THE PLUG HOUSING WHEN SHIPPED TO THE CUSTOMER.
3. DETAILS OF CAVITIES;SEE TABLE-1.

1. 取扱説明書 ; 411-5919
2. ダブルロックは、仮係止状態で出荷される。
3. キャビティ構成はTABLE-1参照。

	FINISH	POS. 極数	P/N	APPLICABLE WIRE RANGE 適用電線
SIGNAL .025	TIN	5	1123343-1	AVSS 0.3-0.5mm ² CAVS0.3-0.5 mm ² CAVUS 0.3-0.5mm ² AVSSH 0.3-0.5mm ²
POWER .040	TIN	2	316836-1	AVS 0.3-0.5mm ² AVSS/CAVS 0.3-0.85mm ² CAVUS 0.3-0.85mm ²
			316838-1	AVS 0.5mm ² AVSS/CAVS 0.85-1.25mm ² CAVUS 1.25mm ²

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN N. YASUDA	07JUL99	 TE Connectivity	
DIMENSIONS: 単位: 概 mm		CHK N. SAI	07JUL99		
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差 = ± 0.2		APVD N. SAI	07JUL99	NAME 名称 025/040 7P PLUG HOUSING, IMMOBILIZER	
		PRODUCT SPEC 製品規格 108-5664		SIZE A3	
MATERIAL 材料 PBT		APPLICATION SPEC 取付適用規格 114-5217,5250		CAGE CODE 00779	DRAWING NO 番号 C=1318801
FINISH 仕上 BLACK		WEIGHT 1.47 g		RESTRICTED TO	
RESTRICTED CUSTOMER				SCALE 尺度 3:1	SHEET OF 1

1470-19 (3/11)