



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF3222-24B	LCD HIGH OUTPUT WHITE 7400°k RGB	1100 @ 0°C	440	5 ± 1	28,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
			TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP					
DRAWN BY L. WENGSTROM			APPV'D BY DATE FD 8/20/02		SIZE A	FSCM NO. 55335	DRAWING NO. BF3222-24B	
RELEASED 8/20/02			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 8/20/02	REVISION DATE	REV. NO.
REV. NO.	DESCRIPTION/ECO NUMBER		APPV'D DATE					SHEET 1 OF 1