

Castors

Nylon Wheel

68 4501, 68 4504 and
68 6801



68 6806



68 7701



68 6701



Features:

- Offers a natural colour injection moulded virgin nylon 6 wheel which is available with plain bearing bore

The wheel can be fitted in the following zinc plated (unless described by stainless) pressed steel castor housings:

- Standard duty top plate swivel and fixed
- There is brake option on the swivel
- Standard duty bolt hole swivel with brake option

Recommended Uses:

This wheel is recommended for standard to medium-heavy duty loads

Working Environment:

Manual handling applications

Suitable for use on compact floors e.g. cement, stone tiles, metallic, epoxy resins etc

Particularly recommended for the food processing industry. Not recommended for use with concentrated organic acids or strong mineral acids

Specifications:

In accordance with ISO 2175. Defines castor and/or wheel application appropriate with environmental conditions-load, speed of use, temperature, floor condition and cycle time

Temperature : -30°C to +80°C

Specification Table

Description	Wheel Diameter	Thread Width	Overall Height	Plate Dimension	Hole Spacing	Hole Width	Offset	Carrying Capacity (kg)	Part Number
Castor, Nylon Wheel, Swivel	80	30	107	100 × 85	80 × 60	9	36	180	68 4501
Castor, Nylon Wheel, Swivel	150	45	192	140 × 110	105 × 80	11	56	300	68 4504

Description	Wheel Diameter	Thread Width	Overall Height	Plate Dimension	Hole Spacing	Hole Width	Offset	Pedal Length	Carrying Capacity (kg)	Part Number
Castor, Nylon Wheel, Swivel*	80	30	107	100 × 85	80 × 60	9	36	120	180	68 6801
Castor, Nylon Wheel, Swivel*	200	50	240	140 × 110	105 × 80	11	56	156	300	68 6806

*Standard duty swivel castor with foot brake

Dimensions : Millimetres

Castors



Nylon Wheel

Description	Wheel Diameter	Thread Width	Overall Height	Plate Dimension	Hole Spacing	Hole Width	Carrying Capacity (kg)	Part Number
Castor, Nylon Wheel, Swivel**	80	30	107	12	80	36	180	68 7701

**Standard duty bolt hole swivel castor

Description	Wheel Diameter	Thread Width	Overall Height	Hole Diameter	Plate Diameter	Offset	Pedal Length	Carrying Capacity (kg)	Part Number
Castor, Nylon Wheel, Swivel***	80	30	107	100 × 85	80 × 60	9	120	180	68 6701

***Standard duty bolt hole castor with foot brake

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk
www.mcmelectronics.com

