

CSB100-891

Slim Type for IBASE IB891 3.5" Disk-Size SBC

CSB100-883

Slim Type for IBASE IB883 3.5" Disk-Size SBC



SBC System

SBC System



Features

- Steel system supports IBASE IB891 3.5-inch Disk-Size SBC
- Onboard Intel® Atom™ Processor N450 SC, 1.66GHz
- Fanless slim box design for a wide variety of applications
- Chassis available in black color
- One 2.5" 160GB SATA HDD
- Wall mount kit included

Specifications

| | |
|--------------------------|--|
| System Mainboard | IB891 |
| CPU Type | Intel® Atom™ Processor N450 |
| System Speed | 1.66GHz |
| Memory | 1x DDR2 SO-DIMM, Max. 2GB |
| Construction | Aluminum & Steel |
| Chassis Color | Black |
| Front Panel External I/O | Power LED, HDD LED, Reset button, Power on/off button, audio, 2x USB ports, Mic-in, Line-out |
| Rear Panel External I/O | 1x VGA, 2x USB ports, 3x COM ports, 2x RJ45 connectors, DC-in jack, 1x WiFi antenna (Reserved) |
| Storage | 1x 2.5" 160GB HDD |
| Power Supply | 60W power adaptor |
| Mounting | Desktop or wall mount (wall mount kit included) |
| Dimensions | 113.6mm(W) x 172.4mm(D) x 52.4mm(H) |
| Operating Temperature | 0°C~ 45°C (32°F~113°F) |
| Storage Temperature | -20°C~80°C (-4°F~176°F) |
| Relative Humidity | 5~90% @ 45°C, (non-condensing) |
| Vibration | CFD: 5 grms / 5~500Hz / random operation HDD: 0.25 grms / 5~500Hz / random operation |

Ordering Information

| | |
|------------|--|
| CSB100-891 | Steel Chassis for IB891 3.5" SBC, 2.5" 250GB SATA HDD, 60W power adaptor |
|------------|--|

Features

- Steel system supports IBASE IB883 3.5-inch Disk-Size SBC
- Onboard Intel® Atom™ Processor N270, 1.6GHz
- Available in black color
- Fanless operation
- One 2.5" HDD drive bay
- Rear panel I/O for USB, DVI, KB/MS, LAN and DC-in jack
- Wall mount kit included

Specifications

| | |
|--------------------------|---|
| System Mainboard | IB883 |
| CPU Type | Intel® Atom™ Processor N270 |
| System Speed | 1.6GHz |
| Memory | 1x DDR2 533 SO-DIMM, Max. 2GB |
| Construction | Steel |
| Chassis Color | Black |
| Front Panel External I/O | Power LED, HDD LED, Power on/off button, Reset button, audio, 2x USB ports |
| Rear Panel External I/O | 1x DVI, 2x USB ports, 2x COM ports, 2x RJ45 connectors, KB/MS connector, DC-in jack |
| Storage | 1x 2.5" HDD drive bay |
| Power Supply | 60W power adaptor |
| Mounting | Desktop or wall mount |
| Dimensions | 113.6mm(D) x 172.4mm(W) x 52.4mm(H) |
| Operating Temperature | 0°C~ 45°C (32°F~113°F) |
| Storage Temperature | -20°C~80°C (-4°F~176°F) |
| Relative Humidity | 5~90% @ 45°C, (non-condensing) |
| Vibration | CFD: 5 grms / 5~500Hz / random operation HDD: 0.25 grms / 5~500Hz / random operation |

Ordering Information

| | |
|---------------|--|
| CSB100-883C-S | Steel Chassis for IB883 3.5" SBC, 2.5" HDD holder, COM, 60W power adaptor |
| CSB100-883C-V | Steel Chassis for IB883 3.5" SBC, 2.5" HDD holder, VGA, 60W power adaptor |
| CSB100-883M-S | Steel Chassis with IB883 3.5" SBC, 2.5" HDD holder, COM, 60W power adaptor |
| CSB100-883M-V | Steel Chassis with IB883 3.5" SBC, 2.5" HDD holder, VGA, 60W power adaptor |

01
Motherboards

02
Disk-Size SBCs

03
CPU Modules

04
PC 104 Plus

05
CPU Cards

06
RISC SBCs

07
Embedded Systems