


MICRO SWITCH
a Honeywell Division

FED. MFG. CODE 91929

**MINIATURE PRECISION
LIMIT SWITCH**

CATALOG LISTING

914CE20-6



2.000 MAX
OPERATING POSITION
IN ALL DIRECTIONS
EXCEPT PULL
(.5 FROM TIP OF
ROD ACTUATOR)

NEOPRENE SEAL

2X \varnothing .200 \pm .010
MOUNTING HOLES
(\varnothing .40 C'BORE
.24 DEEP)

$.300 \pm .010$

1.732 MAX

72.000 MIN

P.V.C. SHEATHED CABLE
18/4 S.J.T.O.

.630 MAX

$.984 \pm .010$

1.575 MAX


NOTES

1 - ZINC HOUSING FINISHED WITH GRAY PAINT

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS

OPERATING FORCE — — — 2 OZ MAX

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

5A - 250 VAC
1/10HP - 125 OR 250 VAC



SCALE FULL

DO NOT
SCALE PRINT

**UNLESS OTHERWISE SPECIFIED
TOLERANCES ARE**

ONE PLACE (.0) \pm .030

TWO PLACE (.00) \pm .015

THREE PLACE (.000) \pm .005

ANGLES \pm

WEIGHT

914CE20-6
M
 DRAWING NUMBER
 ISSUE 3
 REVISIONS
 A CO 69061
 S A V 31 AUG 91
 CHECK
 CHECK
 DDM/CAD
 DRAWN
 S A V 31 AUG 91
 CHECK
 REPLACES
 RELEASE NO. PR-7324