



| REVISIONS | | | |
|-----------|---------------------------|---------|----------|
| REV | DESCRIPTION | DATE | APPROVED |
| A1 | REVISED PER ECO-11-005294 | 14APR11 | HMR |

| | | |
|----------------|--|---|
| HOUSING | STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303 | PASSIVATE PER ASTM-A380 |
| DIELECTRIC | TFE FLUOROCARBON PER ASTM-D-1457 | N/A |
| CENTER CONTACT | BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H | GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290 |
| COMPONENT | MATERIAL | FINISH |

NOTES:
 1. CAPTURED CENTER CONTACT
 2. V.S.W.R.:
 DC-12.4GHz: 1.06+.005fGHz MAX
 12.4-18.0GHz: 0.83+.023fGHz

| | | | | |
|---|------------------------------------|-----------------|--|-------------------------|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1° | DRAWN BY SWA | DATE 6/13/85 | | |
| | CHECKED BY FN | 6/17/85 | | |
| | APPD BY D. GORDON | 6/18/85 | TITLE TYPE N JACK TO SMA JACK ADAPTER | |
| | USE ASSY PROCEDURE NO. A.P. N/A | | SIZE B | CODE IDENT NO. 26805 |
| | CUSTOMER DRAWING | SCALE 5=1 | 1057343-1 | REV A1 |
| | | | SHEET 1 OF 1 | |