

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2006

© COPYRIGHT 2006

Tyco Electronics AMP GmbH

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

AI

-

P	LTR	DESCRIPTION	DATE	DWN	APVD
	C1	ECR-11-018403	07SEP2011	OH	BR
	C2	ECR-11-021475	18NOV2011	GW	BR
	C3	VARIANT 0--3 ADDED PER PCN E-15-007254	12MAY2015	ER	DO
	C4	ECR-15-014241	14OCT2015	GSK	JB

9

1

2

3

4

5

6

7

8

10

11

Ø18

34.6

Ø17.5

STE

0-1103432-1

HC26.Bu.12.C

10A 60V 15kV 3

2

1

SCALE 1:1

1

2

3

4

5

6

7

8

9

10

11

PN 0-1 AS SHOWN

NOT SPECIFIED DIMENSIONS AND NOTES SEE 0-1

NICHT ANGEGEBENE BEMASSUNGEN UND BEMERKUNGEN SIEHE 0-1

3

2

1

SCALE 1:1

STE

0-1103432-1

HC26.Bu.12.C

10A 60V 15kV 3

PN 0-3 AS SHOWN

1	-	-	ADAPTOR RING	PA66-GF25	GREY	SERIES HC26, INSERT	3
1	1	1	RETAINING RING	PA66-GF25	GREY	SERIES HC26, INSERT	2
1	1	1	FEMALE INSERT	PBT-GF10	GREY	SERIES HC26, 12 POS. TYPE III+	1
0-3	0-2	0-1	DESCRIPTION	MATERIAL	SURFACE/COLOR	NOTE	ITEM
QTY/PN			PARTS LIST (PER UNIT)				

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC

1 PLC

2 PLC

3 PLC

4 PLC

ANGLES

±

±

±

±

±

±

MATERIAL

-

FINISH

-

DWN

H.BRAUN

08NOV2007

CHK

T.VETTER

28OCT2008

APVD

T.SCHNURPFIL

28OCT2008

PRODUCT SPEC

108-74097

APPLICATION SPEC

114-74103

WEIGHT

-

NAME

FEMALE INSERT ASS'Y

SERIES HC26, 12-POS., TYPE III+

CIRCULAR HYBRID CONNECTOR

SIZE

A3

CAGE CODE

00779

DRAWING NO

©=1103432

RESTRICTED TO

-

CUSTOMER DRAWING

SCALE 2:1

SHEET 1 OF 1

REV C4

Notes

1

SUITABLE HOUSINGS: SERIES HC26

CUSTOMER DRAWING: 11034XX/33/34/36/37/39/40/70

2

OUTER DIMENSIONS OF INSULATION: MAX. Ø3.2 MM

3

SUITABLE CRIMP CONTACTS:

CUSTOMER DRAWING: 166824

4

SUITABLE SUB-MIN. COAXICON CONTACTS:

CUSTOMER DRAWING: 51565

5

SUITABLE LWL (OPTICS) CONTACTS:

CUSTOMER DRAWING: 216342 AND 1102921

6

SUITABLE INSERTION TOOL:

CUSTOMER DRAWING: 1102855

7

SUITABLE EXTRACTION TOOL:

CUSTOMER DRAWING: 1102855

8

STANDARDS:

DIN EN 61984, DIN EN 60664-1

9

POLARIZATION RIPS

10

PACKAGING PN 0-1:

40 SETS IN A CARTON

11

PACKAGING PN 0-2:

500 SETS IN A CARTON

1470-19 (3/11)