

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0643221029

Status:


Active

Overview:

CMC and CMX Sealed, Hybrid, Modular Connectors

Description:

0.635mm CMC CP Female Terminal, Tin Plated, for Square 0.6mm x 0.6mm Pins, Wire Size 0.75mm²



Documents:	
3D Model	Application Specification AS-64322-001-CH (PDF)
Drawing (PDF)	Application Specification AS-64322-001-FR (PDF)
Product Specification PS-64319-002 (PDF)	Application Specification AS-98420-001 (PDF)
Product Specification PS-64326-001 (PDF)	Application Specification AS-98420-001-CH (PDF)
Application Specification AS-64318-002 (PDF)	Application Specification AS-98420-001-FR (PDF)
Application Specification AS-64318-002-CH (PDF)	Application Specification AS-98420-001-SP (PDF)
Application Specification AS-64318-002-FR (PDF)	Application Specification AS-98420-002 (PDF)
Application Specification AS-64318-002-SP (PDF)	Application Specification AS-98420-002-CH (PDF)
Application Specification AS-64319-002 (PDF)	Application Specification AS-98420-002-FR (PDF)
Application Specification AS-64319-002-CH (PDF)	Application Specification AS-98420-002-SP (PDF)
Application Specification AS-64319-002-FR (PDF)	Packaging Specification PK-98913-001 (PDF)
Application Specification AS-64319-002-SP (PDF)	RoHS Certificate of Compliance (PDF)
Application Specification AS-64322-001 (PDF)	

General	
Product Family	Crimp Terminals
Series	64322
Application	Signal
Comments	* Current tested on a 5 terminals loaded connector, current for temperature increase of 40°C. Current max = 6A for 0.635mm Terminal(0.75mm ² wire)
Crimp Quality Equipment	Yes
Overview	CMC and CMX Sealed, Hybrid, Modular Connectors
Product Name	CMC, CP Terminal
UPC	883906129477
Physical	
Gender	Female
Material - Metal	Phosphor Bronze
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	0.160/g
Packaging Type	Reel
Plating min - Mating	1.524µm, 3.048µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	1.65-1.80mm
Wire Size AWG	18
Wire Size mm ²	0.75
Electrical	
Current - Maximum per Contact	6.0A
Voltage - Maximum	14V DC
Solder Process Data	
Lead-freeProcess Capability	N/A
Material Info	
Reference - Drawing Numbers	
Application Specification	AS-64318-002, AS-64318-002-CH, AS-64318-002-FR, AS-64318-002-SP, AS-64319-002, AS-64319-002-CH,

EU ELV
Compliant

EU RoHS
Compliant

REACH SVHC
Not Contained Per -ED/79/2015 (17 December 2015)

Halogen-Free
Status
Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS
ELV

Green Image
Compliant

Search Parts in this Series
64322 Series

Mates With
CMC Connector [64318](#) , [64319](#) , [64320](#) , [64321](#) , [64326](#)

Use With
CMC Connector [64318](#) , [64319](#) , [64320](#) , [64321](#) , [64326](#)

Application Tooling | [FAQ](#)
Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.
Global

Description	Product #
FineAdjust™ Applicator for CP	0639022000

Packaging Specification
Product Specification
Sales Drawing

AS-64319-002-FR, AS-64319-002-SP, AS-64322-001,
AS-64322-001-CH, AS-64322-001-FR, AS-98420-001,
AS-98420-001-CH, AS-98420-001-FR, AS-98420-001-
SP, AS-98420-002, AS-98420-002-CH, AS-98420-002-
FR, AS-98420-002-SP
PK-98913-001
PS-64319-002, PS-64326-001
SD-64322-001

Crimp 0.6mm
Terminal for CMC
connector
Hand Crimp Tool 0638119200
Extraction Tool 0638132400

This document was generated on 03/29/2016
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION