



The PCI-PIO is a PCI-compatible half-card which provides digital input/outputs and counter/timers. There are 48 TTL-compatible programmable digital input/outputs available from the board. If the controlling devices are used in handshake mode, the handshake lines are available as interrupt sources.

There are also three programmable counter/timers, the enable and clock inputs being available externally, if required. The outputs are accessible externally or as interrupt sources. A 4MHz crystal oscillator is available on board to allow the counter/timers to act as accurate timebases. All input/output lines are available at an industry standard 50 way D-type plug connector. One PCI interrupt line may be selectively driven by the seven interrupt sources on the board, the interrupting source being readily identified by the board.

### Options



1 metre cable with IDC and D type connector (P/N 1371 0071)



50 way screw terminal adapter (P/N 1981-0004)



Windows® 98/2000, NT® and XP® drivers

### Key Features

8255 compatible, inputs & outputs

3 on-board 16 bit Counter Timers (8254 compatible)

Facility to fit pull up/down resistors on inputs

Supplied with demonstration software examples

Fully Universal PCI and Plug -and-play compliant (compatible with 3.3V and 5V buses)

### Technical Specification

<b>Number Of I/O Channels</b>	48 arranged as 2 x 3 x 8 I/O bits
<b>Signal Levels</b>	5 Volt TTL Logic Levels
<b>Outputs</b>	Logic Low Level: 0 Volts (min.) - 0.4 Volts (max.) @ IOL = 2.5mA Logic High Level: 3.5 Volts (min.) - 5 Volts (max.) @ IOH = -400mA
<b>Drive Current</b>	2.5 mA. (Logic Low) Vout = 0.4 Volts, -400 µA (Logic High) Vout = 3.5 Volts
<b>Input Loading</b>	-10 µA (Logic Low), +10 µA (Logic High)
<b>Counters/Timers</b>	3 x 16 Bit. Counter/timers 0,1 and 2 may be cascaded to provide a single 48 bit Counter/timer. All Counter/timers may be clocked externally at a maximum rate of 4 Mhz.
<b>Onboard Oscillator</b>	Frequency 4MHz. Stability ± 100ppm 0 - 70°C
<b>Interrupt Sources</b>	Register selectable to 3 Counter/timer outputs, and 4 PIO handshake control lines.
<b>Interrupt Levels Supported</b>	All PCI interrupts
<b>Address Overhead</b>	16 contiguous addresses in 16 byte block
<b>Board Power Requirement</b>	+3.3 Volts, 0.5 W maximum, +5 Volts, 0.6 W maximum
<b>Signal Connections</b>	1 x 50 way male 'D-type' plug
<b>Dimensions</b>	125 (L) x 91 (H) board only, 135 (L) x 122 (H) x 22 (W) including bracket



INVESTOR IN PEOPLE



BS EN ISO 9001:2000  
Certificate No FM 33069