




REV - DESCRIPT - DATE - APPRVD

.
.
.

4-40 UNC THREAD (2 PLCS)


NOTES:

- COMPONENTS:
 - CONNECTOR: MRJ-538X-0X, RECEPTACLE, 8 CONTACTS.
 - TERMINATION: RJ45, PLUG.
- FEATURE:SEALED CONNECTOR IN THE MATED AND UNMATED CONDITIONS.
- OPERATING TEMPERATURE: -40°C TO +105°C.
- CONNECTOR MEETS CATEGORY CAT5E REQUIREMENTS DESCRIBED IN TIA/EIA-568-B.1 PART 2.
- ENVIROMENT PERFORMANCE: IP67.
- ALL COMPONENTS AND MATERIALS USED FOR CONNECTOR AND PACKAGING ARE ROHS COMPLIANT PER EU DIRECTIVE 2002/95/EC AND AMENDMENTS.



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETER TOLERANCES ARE: DECIMALS ANGLES .XX ± .10 ± 1° .X ± .25		APPROVALS	DATE	Amphenol Canada Corp.		
		DRAWN S.SEMENOV	JAN01/07			
MATERIAL AND FINISH		DESIGNED S.SEMENOV	JAN01/07	TITLE MRJ CONNECTOR WITH RJ45 TERMINATION		
		CHECKED				
		QA APP'D				
REF.		IE APP'D		SIZE C	DWG. NO. P-MRJ-578X-X1	REV. 2A
CODE IDENT. NO.		DWG APP'D A.GREEN	JAN01/07	SCALE 1:0.4	PROJECT MRJ	SHEET 1 OF 2

DO NOT SCALE DRAWING
THIS DOCUMENT COTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE
OR USED FOR MANUFACTURING PURPOSES WITHOUT PERMISSION FROM AMPHENOL CANADA CORP.



REV	DESCRIPT	DATE	APPRVD
.			
.			
.			

RECOMMENDED PANEL CUTOUT



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETER TOLERANCES ARE: DECIMALS ANGLES .XX ± .10 ± 1° .X ± .25 MATERIAL AND FINISH REF. CODE IDENT. NO.		APPROVALS	DATE	Amphenol Canada Corp.		
		DRAWN S.SEMENOV	JAN01/07			
		DESIGNED S.SEMENOV	JAN01/07	TITLE MRJ CONNECTOR WITH RJ45 TERMINATION		
		CHECKED				
		QA APP'D				
		IE APP'D		SIZE C	DWG. NO. P-MRJ-578X-X1	REV. 2A
		DWG APP'D A.GREEN	JAN01/07	SCALE 4:1	PROJECT MRJ	SHEET 2 OF 2

DO NOT SCALE DRAWING
THIS DOCUMENT COTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE
OR USED FOR MANUFACTURING PURPOSES WITHOUT PERMISSION FROM AMPHENOL CANADA CORP.