



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP24V28-2U

BP24V28-2U - External Battery Pack for UPS System

Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 24VDC external battery connector
- Simple installation; 2U rackmount, tower and stack adaptable



Description

BP24V28-2U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 2 rack spaces (2U). Includes heavy gauge cabling with high current DC connector for simple installation.

Compatible UPS Systems - OMNIVS1500XL, OMNIVSINT1500XL, SU750XL, SU750RTXL2U, SU1000XL, SU1000RTXL2Ua, SUINT1000RTXL2Ua, SMART750RML2U, and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP24V28-2U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- NOTE: LIMIT OF 1 BP24V28-2U PER UPS, SEE BP24V70-3U FOR MULTI-PACK COMPATIBILITY

Specifications

BATTERY	
DC system voltage (VDC)	24

Connects to UPS via	Attached cable with red/black 75 amp male DC connector
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	68
Shipping weight (kg)	30.8
Unit Dimensions (HWD/in)	3.5 x 17.5 x 14
Unit Dimensions (HWD/cm)	8.9 x 44.5 x 35.6
Shipping Dimensions (HWD/in)	6.75 x 23.5 x 18.25
Shipping Dimensions (HWD/cm)	17.1 x 59.7 x 46.4
Unit weight (lbs)	56.5
Unit weight (kg)	25.6
Material of construction	Steel
Form factors supported	2U rack/tower
CERTIFICATIONS	
Certifications	CE
WARRANTY	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

Related Items

Optional Products

Related Model	Description	Qty.
WEXT3-BP24V	3-Year Extended Warranty - For All 24V Battery Packs	1
WEXT5-BP24V	5-Year Extended Warranty - For All 24V Battery Packs	1
2-9USTAND	Enables Tower Placement of Rackmount UPS Systems	1
2POSTRMKITWM	Enables 2-Post Rackmount or Wallmount Installation of Select Rackmount UPS Systems	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=3015.

