Industrial

Compact 6240 Series Keyboards



Compact Keyboards with Integrated Touchpad for Industrial Applications

Main Applications

- Rack Mount Systems
- Airlines
- Education/Schools
- Banking
- Medical Equipment
- Automotive Equipment
- POS/POT
- Office/Data Entry
- White Box PCs
- Field Services
- Test Equipment
- Kiosk Applications
- POS/POT
- Manufacturing
- Transport

Key Features

- Full QWERTY Key Layout in Compact 14" Form Factor Combines Maximal Space Efficiency with Uncompromized Alphanumeric Data Entry
- Enhanced US 106 Position Key Layout
- Robust Product Design with IP 54 Spill and Dust Resistant Key Field for Harsh Environments
- Touchpad Ensures Easy Cursor Navigation with Minimal Desktop Surface
- Yellow Status LEDs for Improved Visibility in Rooms with Artificial Illumination
- Numeric Pad includes "00" Key for Fast Currency Typing

Part Numbers

G86-62401EUADAA
Black

G86-62401EUAEAA
Lt. grey

CHERRY®

Industrial

Compact 6240 Series Keyboards

Technical Data

Interface
USB 2.0

Current Input
typ. 35 mA

Touchpad
Resolution: 1000 dpi
Two switch-activated mouse buttons

Cable Length
Approx. 1.85 m

Key Layout
Compact size 106 position US key layout including Windows keys

Weight (without/with packaging)
1.4 kg/1.6 kg

Dimension
360 x 198 x 38 mm (keyboard)
415 x 260 x 50 mm (packaging)

Packaging Units
25 per master carton
8 master cartons per pallet

Keyswitch Lifetime
25 million operations

Storage Temperature
-20°C to 60°C

Operating Temperature
0°C to 50°C

Approvals
cURus, FCC, CE, BSMI, VCCI, C-Tick, GOST-R, WHQL

Delivery Volume
Keyboard, Quick Guide, CDROM

Warranty
2 years

For information on repairs or warranty status contact:
Cherry Technical Support
Phone: 800.510.1689
E-Mail: keyboardsupport@cherrycorp.com

Contact

Call, fax or visit our website for more information.

Last Update: 2/23/10

ZF Electronics Corporation
11200 88th Avenue
Pleasant Prairie, WI 53158

Phone: 262.942.6500
Web: www.cherrycorp.com

E-Mail: cep_sales@zf.com
Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2007 ZF Electronics Corporation

CHERRY®