




LOC	DIST	REVISIONS 変更				
		P	LTR	DESCRIPTION	DATE	DWN APVD
J	-		C	REVISED	15APR2014	H.O N.Y
			D	REVISED	17JUN2014	H.O N.Y

AS SHOWN : 1-2013522-0 (10POS,X-KEY)



10	Y	9	67.5	75.7	73.3	BLACK	2-2013522-0
10	X	9	67.5	75.7	73.3	BLACK	1-2013522-0
7/10	Z	9	67.9	75.7	73.3	BLACK	9-2013522-0
3	Y	2	15.0	23.2	20.4	NATURAL	4-2013522-3
3	X	2	15.0	23.2	20.4	BLACK	1-2013522-3
POS	KEY	n	A	B	C	COLOR	PART NO

1. 材料:ハウジング:熱可塑性ポリエステル樹脂
コンタクト:銅合金
スプリング:ステンレス
2. めっき:(コンタクト接触部):ニッケル下地めっきの上に金めっき0.38μm以上
3. 取扱説明書411-78272参照

- 1.MATERIAL HOUSING:THERMO PLASTIC POLYESTER
CONTACT:COPPER ALLOY
SPRING:SUS
- 2.FINISH(CONTACT AREA):0.38μmMIN GOLD PLATED OVER NICKEL
- 3.SEE INSTRUCTION SHEET 411-78272

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 耗
mm

MATERIAL
材料

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

一般公差 ±0.3, ±5°
0 PLC ±
1 PLC ±
2 PLC ±
3 PLC ±
4 PLC ±
ANGLES ±

FINISH
仕上

DWN
T. KUDO
21APR2008

CHK
S. MANABE
21APR2008

APVD
S. MANABE
21APR2008

PRODUCT SPEC
製品規格
108-78400

APPLICATION SPEC
取付適用規格
-

WEIGHT
-

CUSTOMER DRAWING

TE Connectivity

NAME
名称
DYNAMIC D3900S 7.5mmPITCH
REC ASSY (SPRING CLAMP TYPE)
3-10POS TYPE-A

SIZE
A3

CAGE CODE
00779

DRAWING NO
番号
C-2013522

RESTRICTED TO
-


SCALE
尺度
2:1

SHEET
1


OF
3

REV
D


LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	APVD
J	-			SEE SHEET 1		




10POS(Y-KEY):2-2013522-0





7/10POS(Z-KEY)
CIRCUIT 1~7:9-2013522-0



18.75 26.25



24.1 24.1



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN T. KUDO	21APR2008	 TE Connectivity				
DIMENSIONS: mm		CHK S. MANABE	21APR2008					
		APVD S. MANABE	21APR2008	NAME DYNAMIC D3900S 7.5mmPITCH REC ASSY (SPRING CLAMP TYPE) 3-10POS TYPE-A				
		PRODUCT SPEC 108-78400						
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC -		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
0 PLC ±-		WEIGHT -		A3	00779	C-2013522	-	
2 PLC ±-		CUSTOMER DRAWING						
3 PLC ±-								
4 PLC ±-								
ANGLES ±-								
MATERIAL -		FINISH -		SCALE 2:1		SHEET 2	OF 3	REV D

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY Tyco Electronics Japan G.K.

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR


DESCRIPTION

DATE


DWN

APVD


SEE SHEET 1




3POS(X-KEY): 1-2013522-3





3POS(Y-KEY): 4-2013522-3



9.4 7.5



7.5 9.4



THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±
1 PLC ±
2 PLC ±
3 PLC ±
4 PLC ±
ANGLES ±

MATERIAL

FINISH

DWN 21APR2008

T. KUDO

CHK 21APR2008

S. MANABE

APVD 21APR2008

S. MANABE

PRODUCT SPEC

108-78400

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING



TE Connectivity

NAME
DYNAMIC D3900S 7.5mmPITCH
REC ASSY (SPRING CLAMP TYPE)
3-10POS TYPE-A

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A300779C-2013522

SCALE

2:1

SHEET

3

OF

3

REV

D