



**660-008 (Plug) - 660-009 (Receptacle)
661-001 (EMI Receptacle)
Protective Covers
MIL-C-26482**

MIL-C-26482


Basic Part No. **660-008 M 20 S 6 -04**
 660-008 Plug
 660-009 Receptacle
 661-001 Receptacle
 Finish (Table II)
 Shell Size (Table X)
 Ring or Eyelet Dash No.
 (Tables IV, V, VI, VII)
 Attachment Length (in inches)
 Attachment Type (Table III)



660-008 Plug Cover



660-009 Receptacle Cover



661-001 EMI/RFI Receptacle Cover

TABLE X: SHELL SIZE DIMENSIONS

Shell Size	E Dia	F Max	G Dia Max	H Dia Max	J Max
08	.473 (12.0)	.562 (14.3)	.719 (18.3)	.734 (18.6)	.562 (14.3)
10	.590 (15.0)	.562 (14.3)	.844 (21.4)	.859 (21.8)	.562 (14.3)
12	.750 (19.1)	.562 (14.3)	1.000 (25.4)	1.000 (25.4)	.562 (14.3)
14	.875 (22.2)	.562 (14.3)	1.125 (28.6)	1.125 (28.6)	.562 (14.3)
16	1.000 (25.4)	.562 (14.3)	1.250 (31.8)	1.250 (31.8)	.562 (14.3)
18	1.125 (28.6)	.562 (14.3)	1.375 (34.9)	1.375 (34.9)	.562 (14.3)
20	1.250 (31.8)	.625 (15.9)	1.500 (38.1)	1.500 (38.1)	.562 (14.3)
22	1.375 (34.9)	.625 (15.9)	1.625 (41.3)	1.625 (41.3)	.562 (14.3)
24	1.500 (38.1)	.658 (16.7)	1.750 (44.5)	1.750 (44.5)	.602 (15.3)

See inside back cover fold-out or page 14 for Table II.

Metric dimensions (mm) are indicated in parentheses.

**660-008 (Plug) - 660-009 (Receptacle)
661-001 (EMI Receptacle)
Protective Covers
MIL-C-26482**



66 & 78






TABLE III: ATTACHMENT	
Sym	Attachment Type
D	Bead Chain, Cres., Passivate
F	Wire Rope, Nylon Jacket
G	Nylon Rope
H	Wire Rope, Teflon Jacket
N	No Attachment
R	Wire Rope, PVC Jacket
S	#8 Sash Chain, Cres., Passivate
T	Wire Rope, No Jacket
U	Wire Rope, Polyurethane Jacket with Terminal

TABLE IV: EYELET		
Dash No.	±.010	K DIA (0.3)
01	.140	(3.6)
02	.182	(4.6)
03	.191	(4.9)
04	.197	(5.0)
05	.167	(4.2)
06	.125	(3.2)
07	.218	(5.5)
09	.156	(4.0)
00	No Eyelet	






TABLE V: SPLIT RING STYLE C			
Dash No.	±.015 (0.4)	L Dia.	Dash No.
50	.425 (10.8)		74
52	.485 (12.3)		76
54	.640 (16.3)		78
56	.750 (19.1)		80
58	.890 (22.6)		82
60	1.015 (25.8)		84
62	1.095 (27.8)		86
64	1.130 (28.7)		88
66	1.250 (31.8)		90
68	1.350 (34.3)		92
70	1.390 (35.3)		94
72	1.485 (37.7)		

TABLE VI: SOLID RING STYLE B			
Dash No.	±.015 (0.4)	M Dia.	Dash No.
08	.468 (11.9)		24
10	.593 (15.1)		25
12	.718 (18.2)		27
13	.765 (19.4)		28
14	.844 (21.4)		29
15	.890 (22.6)		30
16	.968 (24.6)		31
17	1.015 (25.8)		32
18	1.093 (27.8)		33
19	1.140 (29.0)		35
20	1.203 (30.6)		36
21	1.265 (32.1)		40
22	1.343 (34.1)		44
23	1.453 (36.9)		48
			118

TABLE VII: SOLID RING STYLE A			
Dash No.	±.015 (0.4)	N Dia.	Dash No.
095	.312 (7.9)		109
100	.391 (9.9)		209
101	.516 (13.1)		110
102	.583 (14.8)		210
103	.641 (16.3)		111
104	.708 (18.0)		211
105	.766 (19.5)		112
205	.788 (20.0)		113
106	.896 (22.2)		213
206	.907 (23.0)		114
107	1.016 (25.8)		214
207	1.025 (26.0)		115
108	1.141 (29.0)		116
308	1.188 (30.2)		117
208	1.203 (30.6)		