XCC3930TS84SGN

absolute encoder Ø 90 multi turn - through shaft 30 mm - SSI 25-bit Gray

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Commercial Status	Commercialised
Range of product	OsiSense XCC
Encoder type	Multiturn absolute encoder
Encoder name	XCC
Product specific application	-
Diameter	3.54 in (90 mm)
Shaft diameter	1.18 in (30 mm)
Shaft type	Through shaft
Resolution	4096 turns/8192 points
Electrical connection	1 male connector M23 radial 12 pins
Output stage	Type SG
Type of output stage	SSI 25-bit gray
[Us] rated supply voltage	1130 V DC
Enclosure material	Zamak

Complementary

Shaft tolerance	H7
Residual ripple	0500 mV
Maximum revolution speed	3600 rpm
Shaft moment of inertia	0.02 lb.in² (56 g.cm²)
Torque value	0.07 lbf.in (0.008 N.m)
Maximum load	8 daN radial 2 daN axial
Output frequency	100500 kHz
Current consumption	0100 mA no-load
Protection type	Reverse polarity protection Short-circuit protection
Physical interface	RS422
Output level	High level: 2 V minimum 20 mA
Surge withstand	1 kV level 2 IEC 61000-4-5
Base material	Aluminium
Shaft material	Stainless steel
Type of ball bearings	6807ZZ
Product weight	2.34 lb(US) (1.06 kg)

Environment

Marking	CE	
Ambient air temperature for operation	14167 °F (-1075 °C)	
Ambient air temperature for storage	-4185 °F (-2085 °C)	
IP degree of protection	IP65 IEC 60529	
Vibration resistance	10 gn (102000 Hz) IEC 60068-2-6	
Shock resistance	30 gn (11 ms) IEC 60068-2-27	
Resistance to electrostatic discharge	8 kV air discharge level 3 IEC 61000-4-2 4 kV contact discharge level 3 IEC 61000-4-2	
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) level 3 IEC 61000-4-3	
Resistance to fast transients	2 kV power ports level 3 IEC 61000-4-4 1 kV signal ports level 3 IEC 61000-4-4	

Ordering and shipping details

Category	22486 - SENSORS, PROXIMITY
Discount Schedule	DS2
GTIN	003389119015745
Nbr. of units in pkg.	1
Package weight(Lbs)	2.33
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	FR

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0701 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months

