Detailed Specifications & Technical Data



8019 Hook-up/Lead - Bus Bar Wire

For more Information please call

1-800-Belden1



Description:

Made in accordance with the performance requirements of Federal Spec. QQ-W-343G. Solid tinned copper conductor. Belden® can certify upon special request compliance to the performance requirements of QQ-W-343S_S1T.

Physical Characteristics (Overall)				
Conductor				
AWG: # Conductors AWG Stranding Conductor Material				
1 18 Solid TC - Tinned Copper				
Circular Mil Area (CMA):	1648			
Overall Cabling				
Overall Nominal Diameter:	1.041 mm			
Mechanical Characteristics (Overall)				
Bulk Cable Weight:	8.929 Kg/Km			
Applicable Specifications and Agency Co	ompliance (Overall)			
Applicable Standards & Environmental Progr	rams			
EU Directive 2000/53/EC (ELV):	Yes			
EU Directive 2002/95/EC (RoHS):	Yes			
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004			
EU Directive 2002/96/EC (WEEE):	Yes			
EU Directive 2003/11/EC (BFR):	Yes			
CA Prop 65 (CJ for Wire & Cable):	Yes			
MII Order #39 (China RoHS):	Yes			
Plenum/Non-Plenum				
Plenum (Y/N):	No			
Electrical Characteristics (Overall)				
Nom. Conductor DC Resistance:				
DCR @ 20°C (Ohm/km) 20.9656				
Related Documents:				

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8019 000100	30 MT	0.227 KG	NONE		18 SOL BUS BAR WIRE
8019 0001000	305 MT	2.722 KG	NONE		18 SOL BUS BAR WIRE



METRIC MEASUREMENT VERSION

8019 Hook-up/Lead - Bus Bar Wire

Revision Number: 1 Revision Date: 05-14-2007

© 2011 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.